



HIGH PERFORMANCE SYNTHETIC



SYNTHETIC



ABRASION



HIGH VISIBILITY



IMPACT



PUNCTURE



TEAR

GL807HT

Synthetic Leather | Nylon | Polycotton | TPR

ANSI/ISEA 105



ANSI / ISEA 138



EN388



2121XP



ANSI/ISEA 105 – ABRASION 6 | PUNCTURE 2
EN388 – ABRASION 2 | CUT 1 | TEAR 2 | PUNCTURE 1 |
CUT TDM-100 X | IMPACT P

Synthetic leather palm with silicone print for outstanding grip // PVC palm patch in high abrasion area // Mesh stretch fabric back for comfort and breathability // Slip-on neoprene cuff // Pull tab for easy on/off access // Hi-vis back for enhanced visibility // Level 2 impact protection // Hangtag for retail display

Suggested Applications

Construction // Demolition // Extraction & Refining // Fracking // General Maintenance // Handling Heavy Materials // Heavy Equipment Operator // Mining // Oil & Gas // Rigging

Glove Breakdown

Cuff: Neoprene
Impact: Thermoplastic Rubber
Palm: Polyurethane + Nylon
Palm Print: Silicone
Palm Patch: Polyvinyl Chloride
Back: Nylon + Spandex

⚠ WARNING: Cancer and Reproductive Harm –P65Warnings.ca.gov
This product contains components that may be a potential risk to allergic reactions (latex in the wrist cuff). Do not use in the event of hypersensitivity signs or a known allergy to latex.

Packaging

	Inner Polybag	Outer Polybag	Case
GL807HT	1 Pair on Hangtag	6	60 Pair
Made in Indonesia			

Product markings may vary // Updated as of 11.23



Glove Sizing

Small	Medium	Large	X-Large	2X-Large	3X-Large
7	8	9	10	11	12

All sizes comply with EN ISO 21420 for comfort, fit and dexterity. Only wear the correct size for your hand. Gloves that are too loose or too tight will restrict movement and will not provide the optimal level of protection.

