

Atoka®

ANSI/ISEA Z87.1-2020 | CAN/CSA Z94.3-20

Integrated nose piece // Soft non-slip rubber temple tips provide non-binding fit // Custom imprinting available

VARIATIONS

Lens and Temples | 6 Variations

	S9110S	Clear
	S9110ST	Clear H2X AF
	S9120S	Gray
	S9120ST	Gray H2X AF
	S9180S	I/O Mirror
	S9180ST	I/O Mirror AF



MATERIALS

Lens	Temples	Temple Tips	Nose Piece	Hinge
Polycarbonate	Polycarbonate	Polyvinyl Chloride (PVC)	Polycarbonate	Polycarbonate

MARKINGS

Part No.	Lens Marking	Temple Marking	Lens Marking Symbols	Temple Marking Symbols	Measurements
S9110S	P Z87 + U6	P Z87 + / P c SEI Z94.3	P: Manufacturer's Mark	Symbols	Weight: 22.2 gm
S9110ST	P Z87 + U6	P Z87 + / P c SEI Z94.3	Z87: ANSI/ISEA Z87.1-2020 standard for eye and face protection devices	P: Manufacturer's Mark	Bridge: 12.7 mm
S9120S	P Z87 + U6 L2.5	P Z87 + / P c SEI Z94.3	+: High Impact	Z87: ANSI/ISEA Z87.1-2020 Standard for Eye and Face Protection Devices	Lens Base: 10 curve
S9120ST	P Z87 + U6 L2.5	P Z87 + / P c SEI Z94.3	S: Special Purpose	+: High Impact	Lens Size Diagonal: 79 mm
S9180S	P Z87 + U6 L1.7	P Z87 + / P c SEI Z94.3	UV Filter Transmittance	 Z94.3: Certified for CAN/CSA Z94.3-20 Standard for Eye and Face Protection Devices	Lens Size Vertical: 44 mm
S9180ST	P Z87 + U6 L1.7	P Z87 + / P c SEI Z94.3	U6: .01% Max Effective Far UV • .1% Max Near UV		Lens Thickness: 2.5 mm
			Visible Light Filters		Overall Length (lens - tip): 157 mm
			L1.7: 55% Max Visible Light		Overall Width (hinge - hinge): 137 mm
			L2.5: 29% Max Visible Light		

Product markings may vary // Updated as of 10.26