



ANTI-FOG
OPTIONS



FOAM PADDED
OPTIONS



RUBBER
NOSE PIECE



CUSTOM
LOGO

Atrex™

ANSI/ISEA Z87.1-2020 + | CAN/CSA Z94.3-2020

Foam padding // Adjustable rubber nose piece //
Co-injected straight-back temples //
Custom imprinting available

VARIATIONS

Black Frame | 3 Variations

- SB10810DT Clear AF
- SB10820DT Gray AF
- SB10880DT I/O Mirror AF

Pearl Gray Frame | 1 Variation

- SPG10810DT Clear AF

Translucent Brown Frame | 1 Variation

- STB10815DT Coffee AF

Red Frame | 1 Variation

- SR10870D Silver Mirror



ACCESSORIES

Restraining Strap
108STRAP

Strap sold separately



MATERIALS

Lens	Nose Piece	Frame	Temples
Polycarbonate	Thermoplastic Rubber (TPR)	Polycarbonate + Foam	Polycarbonate + Thermoplastic Elastomers (TPE)

MARKINGS

Part No.	Lens Marking	Temple Marking	Lens Marking Symbols	Temple Marking Symbols	Measurements
SB10810DT	P Z87 + U6	P Z87 + / P c SEI Z94.3	P: Manufacturer's mark	P: Manufacturer's mark	Weight: 34.22 gm
SB10820DT	P Z87 + U6 L3	P Z87 + / P c SEI Z94.3	Z87: ANSI/ISEA Z87.1-2020 standard for eye and face protection devices	Z87: ANSI/ISEA Z87.1-2020 standard for eye and face protection devices	Bridge: 16 mm
SB10880DT	P Z87 + U6 L1.7	P Z87 + / P c SEI Z94.3	+: High Impact	+: High impact	PD: 64 mm
SPG10810DT	P Z87 + U6	P Z87 + / P c SEI Z94.3	S: Special Purpose	SEI Z94.3: Certified for CAN/CSA Z94.3-20 standard for eye and face protection devices	Lens base: 8 curve
SR10870D	P Z87 + S	P Z87 + / P c SEI Z94.3	UV Filter Transmittance		Lens size diagonal: 63 mm
STB10815DT	P Z87 + U6 L3	P Z87 + / P c SEI Z94.3	U6: .01% max effective far UV • .1% max near UV		Lens size vertical: 37.5 mm
			Visible Light Filters		Lens thickness: 2.0mm
			L1.7: 55% Max Visible Light		Overall length (lens - tip): 166 mm
			L2.5: 29% Max Visible Light		Overall width (hinge - hinge): 136.3 mm
			L3: 18% Max Visible Light		

Product markings may vary // Updated as of 07.26