PYRAMEX

CONICAL BANDED EARPLUGS

BP3000 Series

ANSI/ASA S3.19-1974

NRR 29dB | SNR 29dB

Reusable earplugs // Designed for environments with on- and- off noise hazards // Flexible band can rest around neck when not in use // Conical earplugs that require no roll down

BP3000 Hi-Vis Orange

Earplug Breakdown

Reusable: Yes
Metal Detectable: No
Size: One size fits most
Plug Material: Polyurethane Foam (PU)
Plug Dimensions: 2.8 x 1.75 cm
Plug Shape: Conical
Band Material: Polypropylene (PP)
Band Color: Black
Band Length: 16.5 cm

⚠ WARNING: Cancer and Reproductive Harm –P65Warnings.ca.gov

Product Guidelines

The level of noise entering a person's ear, when hearing protection is worn as directed is closely approximated by the difference between the A-weighted environmental level and the NRR.

Example: 1. The environmental noise level at the ear is 92 dB(A).
2. The NRR is 26 decibels (dB).
3. The level of noise entering the ear is approximately equal to 60 dB(A).

CAUTION: For noise environments dominated by frequencies below 500 Hz, the C-weighted environmental noise level should be used. Improper fit of this device will reduce its effectiveness in attenuating noise. Plugs should be inserted with a gentle rocking; twisting motion while opposite hand is opening ear canal by pulling the top of ear. Although hearing protectors can be recommended for protection against the harmful effects of impulse noise, the Noise Reduction Rating (NRR) is based on the attenuation noise and may not be an accurate indicator of the protection attainable against impulsive noise, such as gunfire.

All hearing protection meets ANSI/ASA S3.19-1974 standards. For more information visit our website or contact your sales representative.