

Cappture™ ANSI • CE • CSA •



Dielectric // Fits over most prescription glasses // Temples extend from browbar to avoid interference with prescription frame's temples // Custom imprinting available

Lens and Temples | 5 Variations

- S9910ST ●●● Clear **H2X** AF
- S9910STM ●●● Clear **H2MAX** AF
- S9920ST ●●● Gray **H2X** AF
- S9930ST ●● Amber **H2X** AF
- S9960ST ●● Infinity Blue **H2X** AF



**WATCH THE
CAPPTURE
VIDEO**



Part No.	Lens Marking	Temple Marking	General Specifications	Materials
S9910ST	P Z87 + U6	P Z87 + / P c SEI Z94.3	Weight: 29.5 gm	Lens: polycarbonate
S9910STM	P Z87 + U6 X	P Z87 + / P c SEI Z94.3	Bridge: 23.1 mm	Nosepiece: polycarbonate
S9920ST	P Z87 + U6 L2.5	P Z87 + / P c SEI Z94.3	Lens base: 2.5 curve	Temple: polycarbonate
S9930ST	P Z87 + U6	P Z87 + / P c SEI Z94.3	Lens size diagonal: 145.7 mm	Hinge: polycarbonate
S9960ST	P Z87 + S	P Z87 + / P c SEI Z94.3	Lens size vertical: 51.5 mm	

Lens Marking Symbols

P: Manufacturer's mark
Z87: ANSI standard for eye and face protection devices

+: High impact

X: Tested Anti-fog

UV Filter Transmittance

U6: .01% max effective far UV • .1% max near UV

Visible Light Filters

L2.5: 29% max visible light

Temple Marking Symbols

P: Manufacturer's mark
Z87: ANSI standard for eye and face protection devices

+: High impact

c SEI Z94.3: CAN/CSA standard for eye and face protection devices

General Specifications

Weight: 29.5 gm
Bridge: 23.1 mm
Lens base: 2.5 curve
Lens size diagonal: 145.7 mm
Lens size vertical: 51.5 mm
Lens thickness: 1.8 mm
Overall length: 160 mm
Overall width: 132.5 mm