

Cappture™ Plus ANSI • CE • CSA •



DIELECTRIC



INCLUDES STRAP

Dielectric // Fits over most prescription glasses
 // Flexible rubber gasket // Temples extend from browbar to avoid interference with prescription frame's temples // Custom imprinting available

Rubber Gasket with Temples | 2 Variations

- ES9910STMRG ●●● Clear **H2MAX** AF
- ES9920STMRG ●●● Gray **H2MAX** AF



WATCH THE CAPPTURE PLUS VIDEO



Part No.	Lens Marking	Temple Marking
ES9910STMRG	2C-1.2 P 1FT KN CE	CE P EN166 FT
ES9920STMRG	5-2.5 P 1FT KN CE	CE P EN166 FT

General Specifications
Weight: 51.7 gm
Bridge: 23.1 mm
Lens base: 2.5 curve
Lens size diagonal: 145.7 mm
Lens size vertical: 51.5 mm
Lens thickness: 1.8 mm
Overall length: 160 mm
Overall width: 132.5 mm

Materials
Lens: polycarbonate
Rubber gasket: polycarbonate & thermoplastic rubbers (TPR)
Nosepiece: polycarbonate
Temple: polycarbonate
Hinge: nylon + polycarbonate

Lens Marking Symbols

Code - field of use
 2 or 3: UV filter
 5 or 6: Solar filter

Colour Perception
 C: Unimpaired colour perception

Protection Class
 1.2 - 6: Degree of visible light filtration

Optical Class
 1: High optical quality - no optical distortion

Mechanical Strength
 F: Low energy impact, resists a 6 mm, .86 g at 45 m/s
 T: Impact protection at extreme temperature conditions

Temple Marking Symbols

Symbols
 CE: Europe standard
 P: Manufacturer's mark
 EN166: CE specification for protective eyewear

Mechanical Strength
 F: Low energy impact
 T: Impact protection at extreme temperature conditions

Symbols
 P: Manufacturer's mark
 K: Resistance to surface damage by fine particles
 N: Filter with anti-fog
 CE: Europe standard