

# Cappture Pro ANSI • CE • UKCA • CSA



Dielectric // Fits over most prescription glasses // Flexible rubber gasket // Full strap with quick release // Passes EN166 3: Droplet and Splash Test // Passes EN166 4: Dust Test // Passes EN166 5: Fine Dust Test

## Rubber Gasket with Strap | 2 Variations

- EGG9910TM ● ● ● Clear **H2MAX AF**
- EGG9920TM ● ● ● Gray **H2MAX AF**



Part No.	Lens Marking	Frame Marking
EGG9910TM	2C-1.2 P 1BT KN CE	CE P EN166 BT 3 4 5 UKCA
EGG9920TM	5-2.5 P 1BT KN CE	CE P EN166 BT 3 4 5 UKCA

General Specifications
Weight: 66.2 gm
PD: 64 mm
Bridge: 31 mm
Lens base: 2.5 curve
Lens size diagonal: 144 mm
Lens size vertical: 52.2 mm
Lens thickness: 2.0 mm
Overall length: 92 mm
Overall width: 178 mm

Materials
Lens: polycarbonate
Rubber gasket: polycarbonate & thermoplastic rubbers (TPR)
Nosepiece: polycarbonate
Strap holder: nylon
Headband: polyester & polyoxymethylene

Lens Marking Symbols
<b>Code - field of use</b> 2 or 3: UV filter 5 or 6: Solar filter
<b>Colour Perception</b> C: Unimpaired colour perception
<b>Protection Class</b> 1.2 - 6: Degree of visible light filtration
<b>Optical Class</b> 1: High optical quality - no optical distortion
<b>Mechanical Strength</b> B: Medium energy impact, resists a 6 mm, .86 g at 120 m/s T: Impact protection at extreme temperature conditions
<b>Symbols</b> P: Manufacturer's mark K: Resistance to surface damage by fine particles N: Filter with anti-fog CE: Certification of European Union

Frame Marking Symbols
<b>Symbols</b> CE: Certification of European Union P: Manufacturer's mark EN166: CE specification for protective eyewear 3: Droplets or splashes of liquids 4: Large dust particles 5: Fine dust test UKCA: Certification for United Kingdom
<b>Mechanical Strength</b> B: Medium energy impact, resists a 6 mm, .86 g at 120 m/s T: Impact protection at extreme temperature conditions