

# Cappture Pro ANSI • CE • CSA



Dielectric // Fits over most prescription glasses // Flexible rubber gasket // Full strap with quick release // Passes D3: Droplet and Splash Test // Passes D4: Dust Test

## Rubber Gasket with Strap | 2 Variations

- GG9910TM ●●● Clear **H2MAX AF**
- GG9920TM ●●● Gray **H2MAX AF**



Part No.	Lens Marking	Temple Marking
GG9910TM	P Z87 + U6 X	P Z87 + D3 D4 / P c SEI Z94.3
GG9920TM	P Z87 + U6 L2.5 X	P Z87 + D3 D4 / P c SEI Z94.3

  

Lens Marking Symbols	Temple Marking Symbols
P: Manufacturer's mark	P: Manufacturer's mark
Z87: ANSI standard for eye and face protection devices	Z87: ANSI standard for eye and face protection devices
+: High impact	+: High impact
X: Tested Anti-fog	D3: Droplet & Splash Test
UV Filter Transmittance	D4: Dust Test
U6: .01% max effective far UV • .1% max near UV	c SEI Z94.3: CAN/CSA standard for eye and face protection devices
Visible Light Filters	
L2.5: 29% max visible light	

General Specifications	Materials
Weight: 66.2 gm	Lens: polycarbonate
PD: 64 mm	Rubber gasket: polycarbonate & thermoplastic rubbers (TPR)
Bridge: 31 mm	Nosepiece: polycarbonate
Lens base: 2.5 curve	Strap holder: nylon
Lens size diagonal: 144 mm	Headband: polyester & polyoxymethylene
Lens size vertical: 52.2 mm	
Lens thickness: 2.0 mm	
Overall length: 92 mm	
Overall width: 178 mm	