



Capstone® 500

ANSI/ISEA Z87.1-2020 + | CAN/CSA Z94.3-2020 | MIL-PRF-32432

Fits over most prescription glasses // Soft vinyl goggle body conforms to facial contours // Goggle provides protection against dust and chemical splash // Removable vent caps allow the user to remove when more ventilation is required or leave in place for unsurpassed chemical splash resistance // Passes D3: Droplet and Splash Test // Passes D4: Dust Test // Some options pass Ballistic MIL-PRF-32432 High Velocity Impact standards

VARIATIONS

Grey Body with Quick Release Strap | 1 Variation

EGG504T Clear H2X AF

i Fits over most prescription glasses.



Part No.	Lens Markings	Frame Markings
EGG504T	2C-1.2 P 1BT KN CE	P EN166 3 4 BT CE UKCA

General Specifications	Materials
Weight: 92 gm	Lens: Polycarbonate
Bridge: 45 mm	Body: Polycarbonate + Polyvinyl Chloride
PD: 68 mm	Headband: Textile Elastic
Lens Base: 5.5 Curve	Nose Piece: Polyvinyl Chloride
Lens Size Diagonal: 154 mm	
Lens Size Vertical: 78 mm	
Lens Thickness: 2.3 mm	
Strap Length: 540 mm	

Lens Marking Symbols	Temple Marking Symbols
Code - Field of Use 2 or 3: UV Filter 5 or 6: Solar Filter	Symbols P: Manufacturer's Mark EN166: CE Specification for Protective Eyewear 3: Droplets or Splashes of Liquids 4: Large Dust Particles CE: Certification for European Union UKCA: Certification for United Kingdom
Colour Perception C: Unimpaired Colour Perception	Mechanical Strength B: Medium Energy Impact, Resists a 6 mm, .86 g at 120 m/s T: Impact Protection at Extreme Temperature Conditions
Protection Class 1.2 - 6: Degree of Visible Light Filtration	
Optical Class 1: High Optical Quality - No Optical Distortion	
Mechanical Strength B: Medium Energy Impact, Resists a 6 mm, .86 g at 120 m/s T: Impact Protection at Extreme Temperature Conditions	
Symbols P: Manufacturer's Mark N: Filter with Anti-Fog CE: Certification of European Union	

Product markings may vary // Updated as of 10.26