



Capstone® 500

ANSI/ISEA Z87.1-2020 + | CAN/CSA Z94.3-2020 | MIL-PRF-32432

Fits over most prescription glasses // Soft vinyl goggle body conforms to facial contours // Goggle provides protection against dust and chemical splash // Removable vent caps allow the user to remove when more ventilation is required or leave in place for unsurpassed chemical splash resistance // Passes D3: Droplet and Splash Test // Passes D4: Dust Test // Some options pass Ballistic MIL-PRF-32432 High Velocity Impact standards

VARIATIONS

Gray Body with Quick Release Strap | 4 Variations

- GG504T Clear H2X AF
- GG504TM Clear H2MAX AF
- GG504TIR3 3.0 IR Filter H2X AF
- GG504TIR5 5.0 IR Filter H2X AF

Chemical Green Body with Neoprene Strap | 1 Variation

- GC504TN Clear H2X AF



i Fits over most prescription glasses.

Part No.	Lens Markings	Frame Markings
GG504T	P Z87 + U6	P Z87 + D3 D4 / P c SEI Z94.3
GG504TM	P Z87 + U6 X	P Z87 + D3 D4 / P c SEI Z94.3
GG504TIR3	P Z87 + W3	P Z87 + D3 D4
GG504TIR5	P Z87 + W5	P Z87 + D3 D4
GC504TN	P Z87 + U6	P Z87 + D3 D4

General Specifications	Materials
Weight: 92 gm	Lens: Polycarbonate
Bridge: 45 mm	Body: Polycarbonate + Polyvinyl Chloride
PD: 68 mm	Headband: Textile Elastic
Lens Base: 5.5 Curve	Nose Piece: Polyvinyl Chloride
Lens Size Diagonal: 154 mm	
Lens Size Vertical: 78 mm	
Lens Thickness: 2.3 mm	
Strap Length: 540 mm	

Lens Marking Symbols	Frame Marking Symbols
P: Manufacturer's Mark	P: Manufacturer's Mark
Z87: ANSI Standard for Eye and Face Protection Devices	Z87: ANSI Standard for Eye and Face Protection Devices
+: High Impact	+: High Impact
W: Welding Filter	D3: Droplet & Splash Test
X: Tested Anti-Fog	D4: Dust Test
UV Filter Transmittance	CS Z94.3: CAN/CSA Standard for Eye and Face Protection Devices
U6: .01% Max Effective Far UV	
.1% Max Near UV	

Product markings may vary // Updated as of 10.25