

Capstone® 600 ANSI • CE • CSA • Ballistic •



Fits over most prescription glasses // Indirect ventilation system prevents fogging // Includes interchangeable cloth and neoprene straps // Co-material goggle provides superior protection against dust entry and chemical splash // Thermoplastic (TPE) body with universal nose bridge is flexible and contours to the user's face // Passes D3: Droplet and Splash Test // Passes D4: Dust Test // Passes Ballistic MIL-PRF-32432 High Velocity Impact standards

Gray Body with Adjustable Strap | 1 Variation

● G604T2 ● ● ● Clear H2XAF

i Fits over most prescription glasses.



Part No.	Lens Markings	Frame Markings
G604T2	P Z87 + U6	P Z87 + D3 D4 / P c SEI Z94.3
Lens Marking Symbols		Frame Marking Symbols
P: Manufacturer's mark		P: Manufacturer's mark
Z87: ANSI standard for eye and face protection devices		Z87: ANSI standard for eye and face protection devices
+: High impact		+: High impact
UV Filter Transmittance		D3: Droplet & Splash Test
U6: .01% max effective far UV • .1% max near UV		D4: Dust Test
		c SEI Z94.3: CAN/CSA standard for eye and face protection devices

General Specifications
Weight: 84 gm
PD: 68 mm
Bridge: 45 mm
Lens base: 6 curve
Lens size diagonal: 167 mm
Lens thickness: 2.3 mm
Strap length: 540 mm

Materials
Lens: polycarbonate
Body: polypropylene & thermoplastic elastomers
Frame insert: thermoplastic vulcanizates
Headband: polyester
Nosepiece: thermoplastic elastomers
Strap holder: nylon & styrene-butadiene rubber