



Capstone® 600

ANSI/ISEA Z87.1-2020 + | CAN/CSA Z94.3-2020 | MIL-PRF-32432

Fits over most prescription glasses // Indirect ventilation system prevents fogging // Includes interchangeable cloth and neoprene straps // Co-material goggle provides superior protection against dust entry and chemical splash // Thermoplastic (TPE) body with universal nose bridge is flexible and contours to the user's face // Passes D3: Droplet and Splash Test // Passes D4: Dust Test // Passes Ballistic MIL-PRF-32432 High Velocity Impact standards

VARIATIONS

Gray Body with Adjustable Strap | 1 Variation

● G604T2 Clear **H2X** AF

i Fits over most prescription glasses.



Part No.	Lens Markings	Frame Markings
G604T2	P Z87 + U6	P Z87 + D3 D4 / P c SEI Z94.3

General Specifications	Materials
Weight: 84 gm	Lens: Polycarbonate
Bridge: 45 mm	Body: Polypropylene + Thermoplastic Elastomers
PD: 68 mm	Frame Insert: Thermoplastic Vulcanizates
Lens Base: 6 Curve	Headband: Polyester
Lens Size Diagonal: 167 mm	Nose Piece: Thermoplastic Elastomers
Lens Thickness: 2.3 mm	Strap Holder: Nylon + Styrene-Butadiene Rubber
Strap Length: 540 mm	

Lens Marking Symbols	Frame Marking Symbols
P: Manufacturer's Mark	P: Manufacturer's Mark
Z87: ANSI Standard for Eye and Face Protection Devices	Z87: ANSI Standard for Eye and Face Protection Devices
+: High Impact	+: High Impact
UV Filter Transmittance	D3: Droplet & Splash Test
U6: .01% Max Effective Far UV	D4: Dust Test
.1% Max Near UV	c Z94.3: CAN/CSA Standard for Eye and Face Protection Devices

Product markings may vary // Updated as of 11.25