

Capstone® Shield

ANSI/ISEA Z87.1-2020 + | CAN/CSA Z94.3-2020 | MIL-PRF-32432

Fully adjustable elastic band // Fits over most prescription glasses // Lens is coated to prevent fogging // Soft vinyl goggle body conforms to facial contours // Goggles pass the D3: Droplet and Splash Test and D4: Dust Test when vent caps are on // Some goggles options pass Ballistic MIL-PRF-32432 High Velocity Impact standards // Removable vent caps allow the user to remove when more ventilation is required or leave in place for unsurpassed chemical splash resistance // Goggle combined with removable shield provides full face protection // Four ventilation holes provide airflow // Ratchet shield allows user to open or close in three positions for adjustment // Polycarbonate shield conforms to the face offering increased impact and dust protection

VARIATIONS

Lens and Shield | 2 Variations

- GG504TSHIELD Clear **H2X** AF
- GG524TSHIELD Gray **H2X** AF

i Fits over most prescription glasses.



SHIELD ACCESSORIES



Capstone Face Shield and Strap

CAPSHIELD


Ratcheting shield includes strap and clips allowing the user to add to either of the Capstone 500 Series goggles // Sold as a replacement shield for GG504TSHIELD



Disposable Capstone Shield Visors

VPACK6

Pack of 6 clear disposable, tear-off visors, suitable for high dust or muddy working environments



Materials – Goggle

Lens: Polycarbonate
Body: Polycarbonate + Polyvinyl Chloride (PVC)
Nose Piece: Polyvinyl Chloride (PVC)
Hinge: Polycarbonate (PC) + Nylon
Strap: Polyester
Quick release: Polyoxymethylene (POM)

Materials – Shield

Shield: Polycarbonate
Holder: Polycarbonate
Strap: Polyester

Materials – Visor

Visor: Polyethylene Terephthalate (PET)

General Specifications – Goggle

Weight: 132 gm
PD: 68 mm
Lens Base: 5.5 Curve
Lens Size Diagonal: 154 mm
Lens Size Vertical: 78 mm
Lens Thickness: 2.3 mm
Overall Length (lens - tip): 91 mm
Overall Width (hinge - hinge): 180 mm
Strap Length: 232–365 mm

General Specifications – Shield

Weight: 78 gm
Shield Size: 195.58 mm x 177.64 mm
Shield Thickness: 2.0 mm

General Specifications – Visor

Weight: 2.4 gm
Visor Size: 32.4 mm x 6.9 mm
Visor Thickness: 0.1 mm
Bridge: 3.3 mm

Part No.	Lens Marking	Frame Marking	Shield Marking
GG504TSHIELD	PZ87+ U6	PZ87 + D3 D4 / P c SEI Z94.3	P Z87 + / P c SEI Z94.3
GG524TSHIELD	PZ87+ U6 L2.5	PZ87 + D3 D4 / P c SEI Z94.3	P Z87 + / P c SEI Z94.3
CAPSHIELD	—	—	P Z87 +

Lens Marking Symbols

P: Manufacturer's Mark
+: High Impact
W: Welding Filter
X: Tested Anti-Fog
UV Filter Transmittance
U6: .01% Max Effective Far UV •
.1% Max Near UV
Visible Light Filters
L1.3: 85% Max. Visible Light
L2.5: 29% Max Visible Light

Temple Marking Symbols

P: Manufacturer's Mark
Z87: ANSI Standard for Eye and Face Protection Devices
+: High Impact
D3: Droplet & Splash Test (Goggle Only)
D4: Dust Test (Goggle Only)
cSEI Z94.3: CAN/CSA Standard for Eye and Face Protection Devices

Shield Marking Symbols

P: Manufacturer's Mark
Z87: ANSI Standard for Eye and Face Protection Devices
+: High Impact
cSEI Z94.3: CAN/CSA Standard for Eye and Face Protection Devices

Product markings may vary // Updated as of 10.25