

Full Frame Interchangeable Strap Foam Padded Safety Glasses

Garthage®

ANSI CSA



Rubber
Nosepiece



Foam
Padding



Anti-Fog



Ultraviolet
Protection



Scratch
Resistant

FEATURES

Rubber nosepiece

Indirect vented foam padded carriage

Interchangeable temples/strap

MODEL NO. STYLE NO.

EG410 CHB410DTP

● Clear Anti-fog

EG418 CHB418DTP

● Sandstone Bronze Anti-fog

EG420 CHB420DTP

● Gray Anti-fog

Available in a Carhartt polybag
Carhartt packaging design subject to change



Model No: EG410
Style No: CHB410DTP



GENERAL SPECIFICATIONS

Weight: 43.7 gm

Bridge: 15 mm

Lens base: 8 curve

Lens size diagonal: 68 mm

Lens size vertical: 40 mm

Lens thickness: 2.0 mm

Overall length (lens - tip): 130 mm

Overall width (hinge - hinge): 134 + 1 mm

Closest point between temple tips: 80 + 5 mm

Closest point between lens: 17 mm

MATERIALS

Lens: polycarbonate

Closed cell foam: nylon and ethylene-vinyl acetate (EVA)

Frame: nylon

Temple: nylon

Temple tips: thermoplastic rubbers (TPR)

Nose pads: thermoplastic rubbers (TPR)

Screw: stainless steel

LENS + FRAME MARKING SYMBOLS

P: Manufacturer's mark

Z87: ANSI standard for eye and face protection devices

+: High impact

S: Special purpose

c SEI Z94.3: CAN/CSA standard for eye and face protection devices

MODEL NO.	STYLE NO.	LENS MARKING	FRAME MARKING
EG410	CHB410DTP	P+	P Z87+ / P c SEI Z94.3
EG418	CHB418DTP	P+S	P Z87+ / P c SEI Z94.3
EG420	CHB420DTP	P+S	P Z87+ / P c SEI Z94.3