PYRAMEX

ANTI-FOG OPTIONS | H2X OPTIONS | INCLUDES STRAP | VENTED FRAME | CUSTOM LOGO | REMOVABLE TEMPLE STRAP

Crossovr™

ANSI/ISEA Z87.1-2020+ | CAN/CSA Z94.3-20

Removable indirect vented rolled rubber gasket // Removable, adjustable temple strap with quick release // Custom imprinting available



VARIATIONS

Black and Gray Frame | 3 Variations

- SBG10610DT Clear H2X AF
- SBG10620DT Gray H2X AF
- SBG10680DT I/O Mirror AF

Gray and Lime Frame | 1 Variation

- SGL10610DT Clear H2X AF

SBG106



SGL106

MATERIALS

Lens	Rubber Gasket	Temples	Temple Strap	Hook For Temple Strap	Takeup Loop For Strap
Polycarbonate	Polycarbonate + Thermoplastic Rubbers (TPR)	Polycarbonate	Polyester	Nylon	Nylon

MARKINGS

Part No.	Lens Marking	Temple Marking
SBG10610DT	P Z87 + U6	P Z87 + / P c SEI Z94.3
SBG10620DT	P Z87 + U6 L2.5	P Z87 + / P c SEI Z94.3
SBG10680DT	P Z87 + U6 L1.7	P Z87 + / P c SEI Z94.3
SGL10610DT	P Z87 + U6	P Z87 + / P c SEI Z94.3

Lens Marking Symbols

P: Manufacturer's mark

Z87: ANSI/ISEA Z87.1-2020 standard for eye and face protection devices

+: High Impact

UV Filter Transmittance

U6: .01% max effective far UV • .1% max near UV

Visible Light Filters

L1.7: 55% Max Visible Light

L2.5: 29% Max Visible Light

Temple Marking Symbols

P: Manufacturer's mark

Z87: ANSI/ISEA Z87.1-2020 standard for eye and face protection devices

+: High impact

c SEI Z94.3: Certified for CAN/CSA Z94.3-20 standard for eye and face protection devices

Measurements

Weight: 32.9 gm

Bridge: 13.6 mm

PD: 64 mm

Lens base: 9 curve

Lens size diagonal: 78.6 mm

Lens size vertical: 46.8 mm

Lens thickness: 2.0 mm

Overall length (lens - tip): 170 mm

Overall width (hinge - hinge): 130.5 mm

Closest point between lens: 9.5 mm

Strap Length: 165-195 mm

Product markings may vary // Updated as of 11.26