PYRAMEX

H2X OPTIONS | INCLUDES STRAP | VENTED FRAME | CUSTOM LOGO | REMOVABLE TEMPLE STRAP

Crossovr™

ANSI/ISEA Z87.1-2020+ | CAN/CSA Z94.3-20 | CE/UKCA EN166

Removable indirect vented rolled rubber gasket // Adjustable detachable strap with quick release // Removable temple strap // Custom imprinting available



ESGL106

VARIATIONS

Black and Gray Frame | 1 Variation

ESBG10610DT Clear H2X AF

Gray and Lime Frame | 1 Variation

ESGL10610DT Clear H2X AF

MATERIALS

Lens	Rubber Gasket	Temples	Temple Strap	Hook For Temple Strap	Takeup Loop For Strap
Polycarbonate	Polycarbonate + Thermoplastic Rubbers (TPR)	Polycarbonate	Polyester	Nylon	Nylon

MARKINGS

Part No.	Lens Marking	Temple Marking
ESBG10610DT	2C-1.2 P 1FT CE	CE P EN166 3 FT
ESBG10620DT	5-2.5 P 1FT CE	CE P EN166 3 FT
ESGL10610DT	2C-1.2 P 1FT CE	CE P EN166 3 FT

Product markings may vary // Updated as of 09.26

Lens Marking Symbols

Code - field of use
2 or 3: UV Filter
5 or 6: Solar Filter

Colour Perception
C: Unimpaired Colour Perception

Protection Class
1.2 - 6: Degree of Visible Light Filtration

Optical Class
1: High Optical Quality - No Optical Distortion

Mechanical Strength
F: Low Energy Impact, Resists a 6 mm, .86 g at 45 m/s
T: Impact Protection at Extreme Temperature Conditions

Symbols
CE: Europe Standard
P: Manufacturer's Mark

Temple Marking Symbols

Symbols
CE: Europe Standard
P: Manufacturer's Mark
EN166: CE Specification for Protective Eyewear
3: Droplets or Splashes of Liquids

Mechanical Strength
F: Low Energy Impact
T: Impact Protection at Extreme Temperature Conditions

Measurements

Weight: 32.9 gm
Bridge: 13.6 mm
PD: 64 mm
Lens Base: 9 curve
Lens Size Diagonal: 78.6 mm
Lens Size Vertical: 46.8 mm
Lens Thickness: 2.0 mm
Overall Length (lens - tip): 170 mm
Overall Width (hinge - hinge): 130.5 mm
Closest Point Between Lens: 9.5 mm
Strap Length: 165-195 mm