

Defiant[®] Jumbo

ANSI • CE/UKCA •

Jumbo size for use over prescription spectacles
// Tilt type adjustment allows optimum visibility
// Temples adjust to four settings // Passes
EN166 3 & 4, liquid droplets and large dust

Black Temples | 1 Variation

● ESB 1010SJ • ● Clear Jumbo



MATERIALS

Lens: Polycarbonate
Nosepiece: Polycarbonate
Temples: Polycarbonate
Hinge: Nylon
Screw: Stainless Steel

MARKINGS

General Specifications	Part No.	Lens Markings	Frame Markings
Weight: 45 gm	ESB 1010SJ	2C-1.2 P 1 S CE	CE P EN166 3 4 S UKCA
Bridge: 34.4 mm			
PD: 68 mm			
Lens base: 2.25 curve			
Lens size diagonal: 157.8 mm			
Lens size vertical: 66 mm			
Lens thickness: 2.2 mm			
Overall Width (Hinge-Hinge) : 160 mm			
Materials	Lens Marking Symbols	Frame Marking Symbols	
Lens: polycarbonate	Code - field of use	Symbols	
Side Shield: polycarbonate	2 or 3: UV filter	P: Manufacturer's mark	
Nosepiece: Bridge-Polycarbonate	5 or 6: Solar filter	EN 166: CE specification for protective eyewear	
Sleeve (on temple): nylon 6.6	Color perception	3: Liquid droplets or splashes	
Temple: nylon 6.6	C: Unimpaired color perception	4: Large dust particles	
Hinge: nylon 6.6	Protection class	CE: Certification for European Union	
Screw: brass	1.2 - 6: Degree of visible light filtration	UKCA: Certification for United Kingdom	
	Optical class	Mechanical Strength	
	1: High optical quality - no optical distortion	S: Extra strong	
	Mechanical Strength		
	S: Extra strong, resists a 22mm, 43g at 120 m/s		
	P: Manufacturer's mark		
	CE: Certification for European Union		