



ADJUSTABLE
TEMPLES



RATCHETING
TEMPLES

Defiant®

ANSI/ISEA Z87.1-2020 +
Tilt type adjustment allows optimum
visibility // Temples adjust to four
settings // Custom imprinting available

VARIATIONS

Black Temples | 1 Variation
SB1010S Clear



Defiant® Jumbo

ANSI/ISEA Z87.1-2020 + | CE/UKCA EN 166



VARIATIONS

Black Temples | 1 Variation
SB1010SJ Clear Jumbo

MATERIALS

Lens	Temples	Hinge	Nose Piece	Screw
Polycarbonate	Polycarbonate	Nylon	Polycarbonate	Stainless Steel

MARKINGS

Part No.	Lens Marking	Temple Marking	Lens Marking Symbols	Temple Marking Symbols	General Specifications
SB1010S	P Z87+ U6	P Z87 +	P: Manufacturer's mark Z87: ANSI standard for eye and face protection devices +: High impact UV Filter Transmittance U6: .01% max effective far UV • .1% max near UV	P: Manufacturer's mark Z87: ANSI standard for eye and face protection devices +: High impact	Weight: 39 gm 45 gm (Jumbo) PD: 68 mm 68 mm (Jumbo) Bridge: 29.5 mm 34 mm (Jumbo) Lens base: 4.25 curve 2.5 curve (Jumbo) Lens size diagonal: 135.5 mm 157.8 mm (Jumbo) Lens size vertical: 60.8 mm 66 mm (Jumbo) Lens thickness: 2.3 mm 2.2 mm (Jumbo) Overall length (hinge - tip): 145-161 mm 143-159 mm (Jumbo) Overall width (hinge - hinge): 141.5 mm 160 mm (Jumbo)
SB1010SJ	P Z87+ U6	P Z87 +			

Product markings may vary // Updated as of 11.25