

Drop Zone®

ANSI/ISEA Z87.1-2020+ | MIL-PRF-32432



Stylish contoured temples // Extremely lightweight // Rubber nose piece for non-slip, all day comfort // Easy to change replacement lenses // Kit includes removable temples, crush-resistant, neoprene storage case, and four interchangeable H2X anti-fog lenses // Packaged in a free standing clamshell for countertop or pegboard display // Passes MIL-PRF-32432 High Velocity Impact Standards

Black Temples | 4 Variations

VGSB88KIT

-  Clear **H2X**
-  Forest Gray **H2X**
-  Orange **H2X**
-  Vermilion **H2X**



Part No.	Lens Markings	Frame Markings	General Specifications	Materials
Clear H2X	P Z97 + U6	P Z87 +	Weight: 29.5 gm	Lens: Polycarbonate
Forest Gray H2X	P Z97 + U6	P Z87 +	Bridge: 23.8 mm	Temple: Polycarbonate
Orange H2X	P Z87 + S	P Z87 +	PD: 64 mm	Temple Tips: Thermoplastic Rubber (TPR)
Vermilion H2X	P Z87 + S	P Z87 +	Lens Base: 7 curve	Nose Piece: Polycarbonate + Thermoplastic Rubber (TPR)
			Lens Thickness: 2.2 mm	Screw: Stainless Steel
			Lens Size Diagonal: 134.4 mm	Hinge: Polycarbonate
			Lens Size Vertical: 52.5 mm	
			Overall Length (lens-tip): 167 mm	
			Overall Width (hinge-hinge): 135.5 mm	
			Closest Point Between Lens: 75 mm	

Lens Marking Symbols	Frame Marking Symbols
P: Manufacturer's Mark	P: Manufacturer's Mark
Z87: ANSI Standard for Eye and Face Protection Devices	Z87: ANSI Standard for Eye and Face Protection Devices
+: High Impact	+: High Impact
S: Special Purpose	
UV Filter Transmittance	
U6: .01% Max Effective Far UV • .1% Max Near UV	

Product markings may vary // Updated as of 11.25