

Emerge ANSI • CE • CSA •



Soft nosepiece provides comfort for extended use // Rx options accommodate an Rx lens to the maximum of +3 to -3 diopters // Dual lens design with full eye protection // Custom imprinting available

Black Frame | 2 Variations

- SB7950SF ●● 5.0 IR Filter
- SB7960SF ●● 3.0 IR Filter

Black Frame | 1 Variation

- SB7910DRX ●●● Clear

Translucent Gray Frame | 1 Variation

- SG7910DRX ●●● Clear

i Frame must be presented to your optometrist in order to be fitted with prescription lenses.



Part No.	Lens Marking	Temple Marking
SB7950SF	P+W5	P Z87 + / P c SEI Z94.3
SB7960SF	P+W3	P Z87 + / P c SEI Z94.3
SB7910DRX	P+U6	P Z87 -2+ / P c SEI Z94.3
SG7910DRX	P+U6	P Z87 -2+ / P c SEI Z94.3

Lens Marking Symbols

P: Manufacturer's mark
 +: High impact
 W: Welding filter
UV Filter Transmittance
 U6: .01% max effective far UV • .1% max near UV

Temple Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 - 2: Rx
 +: High impact
 c SEI Z94.3: CAN/CSA standard for eye and face protection devices

General Specifications

Weight: 30 gm
 PD: 68 mm
 Bridge: 13 mm
 Lens base: 6 curve
 Lens size diagonal: 58 mm
 Lens size vertical: 42.5 mm
 Lens thickness: 2.2 mm
 Overall length (lens - tip): 163 mm
 Overall width (hinge - hinge): 135 mm
 Closest point between temple tips: 83 mm
 Closest point between lens: 17.7 mm

Materials

Lens: polycarbonate
 Frame: nylon
 Temples: polycarbonate
 Hinge: polycarbonate
 Screw: stainless steel
 Nosepiece: polyvinyl chloride (PVC)