PYRAMEX

H2X OPTIONS | H2MAX OPTIONS | DIELECTRIC | ADJUSTABLE NOSE PIECE

RUBBER NOSE PIECE | CO-INJECTED TEMPLES | FOAM PADDED OPTIONS

Endeavor™ Plus

ANSI/ISEA Z87.1-2020 + | CAN/CSA Z94.3-2020

Built-in brow guard // Special dielectric hinge design // Curved co-injected temples // One-piece wraparound lens // Soft adjustable nose piece // Foam padding is available in select options // Custom imprinting available

Mirror lens options are not dielectric due to the metal powder in lens coating

VARIATIONS

Black and Gray Temples | 5 Variations

	SBG9610S	Clear
	SBG9610ST	Clear **H2X** AF
	SBG9620S	Gray
	SBG9620ST	Gray **H2X** AF
	SBG9680S	I/O Mirror

SBP96

Black and Green Temples | 4 Variations

	SBGR9610S	Clear
	SBGR9610ST	Clear **H2X** AF
	SBGR9620S	Gray
	SBGR9680S	I/O Mirror

SBGR96

Black and Gray Temples with Foam Padding | 2 Variations

	SBG9610STMFP	Clear **H2MAX** AF
	SBG9620STMFP	Gray **H2MAX** AF

SBG96FP

Black and Pink Temples | 1 Variation

	SBP9610S	Clear

SBP96

Black and Green Temples with Foam Padding | 2 Variations

	SBGR9610STMFP	Clear **H2MAX** AF
	SBGR9620STMFP	Gray **H2MAX** AF

SBGR96FP

PYRAMEX

H2X OPTIONS

H2MAX OPTIONS

DIELECTRIC

ADJUSTABLE NOSE PIECE

RUBBER NOSE PIECE

CO-INJECTED TEMPLES

FOAM PADDED OPTIONS

Part No.	Lens Marking	Temple Marking
SBG9610S	P Z87 + U6	P Z87 + / P c SEI Z94.3
SBG9610ST	P Z87 + U6	P Z87 + / P c SEI Z94.3
SBG9610STMFP	P Z87 + U6 X	P Z87 + / P c SEI Z94.3
SBG9620S	P Z87 + U6 L2.5	P Z87 + / P c SEI Z94.3
SBG9620ST	P Z87 + U6 L2.5	P Z87 + / P c SEI Z94.3
SBG9620STMFP	P Z87 + U6 L2.5 X	P Z87 + / P c SEI Z94.3
SBG9680S	P Z87 + U6 L1.7	P Z87 + / P c SEI Z94.3
SBGR9610S	P Z87 + U6	P Z87 + / P c SEI Z94.3
SBGR9610ST	P Z87 + U6	P Z87 + / P c SEI Z94.3
SBGR9610STMFP	P Z87 + U6 X	P Z87 + / P c SEI Z94.3
SBGR9620S	P Z87 + U6 L2.5	P Z87 + / P c SEI Z94.3
SBGR9620STMFP	P Z87 + U6 L2.5 X	P Z87 + / P c SEI Z94.3
SBGR9680S	P Z87 + U6 L1.7	P Z87 + / P c SEI Z94.3
SBP9610S	P Z87 + U6	P Z87 + / P c SEI Z94.3

General Specifications

Weight: 23.5 gm (without foam)
31.03 gm (with foam)

Lens Base: 9.5 Curve

Lens Size Diagonal: 74 mm

Lens Size Vertical: 44.2 mm

Lens Thickness: 1.8 mm

Overall Length (lens - tip): 164 mm

Overall Width (hinge - hinge): 124.7 mm

Materials

Lens: Polycarbonate

Temples: Polycarbonate & Thermoplastic Elastomers (TPE)

Hinge: Polycarbonate

Side Shields: Polycarbonate

Nose Piece: Polycarbonate + Thermoplastic Rubbers (TPR)

Foam Gasket: Nylon + Ethylene-Vinyl Acetate(EVA) Foam

Lens Marking Symbols

P: Manufacturer's Mark

Z87: ANSI Standard for Eye and Face Protection Devices

+: High Impact

X: Tested Anti-Fog

UV Filter Transmittance

U6: .01% Max Effective Far UV • .1% Max Near UV

Visible Light Filters

L1.7: 55% Max. Visible Light

L2.5: 29% Max Visible Light

Temple Marking Symbols

P: Manufacturer's Mark

Z87: ANSI Standard for Eye and Face Protection Devices

+: High Impact

c SEI Z94.3: CAN/CSA Standard for Eye and Face Protection Devices

Product markings may vary // Updated as of 11.26