



Ever-Lite® ANSI • CE • CSA •



Soft nosepiece for snug fit // Slim co-injected temples // Lightweight spectacle – 22 gm // Custom imprinting available



Black Frame | 17 Variations

- SB8610D ••• Clear
- SB8610DT ••• Clear H2MAX AF
- SB8610DTM ••• Clear H2MAX AF
- SB8620D ••• Gray
- SB8620DT ••• Gray H2MAX AF
- SB8620DTM ••• Gray H2MAX AF
- SB8623D •• Dark Gray
- SB8623DT •• Dark Gray H2MAX AF
- SB8624D ••• Photochromic

- SB8625DTM •• Light Gray H2MAX AF
- SB8630D ••• Amber
- SB8660D •• Infinity Blue
- SB8660DT •• Infinity Blue H2MAX AF
- SB8660DTM ••• Infinity Blue H2MAX AF
- SB8665D •• Ice Blue Mirror
- SB8680D ••• I/O Mirror
- SB8680DT ••• I/O Mirror AF

Black and Lime Frame | 2 Variations

- SBL8610DTM •• Clear H2MAX AF
- SBL8620DTM •• Gray H2MAX AF



Photochromic lenses change from clear to dark after exposure to direct UV light. Lenses change from dark to clear after removal from UV light.

Ever-Lite® Readers ANSI • CSA •



Soft nosepiece for snug fit // Slim co-injected temples // Lightweight spectacle – 22 gm // Custom imprinting available

Black Frame | 14 Variations

- | | |
|--|---------------------------------------|
| SB8610R15 •• Clear +1.5 Mag | SB8620R15 •• Gray +1.5 Mag |
| SB8610R15TM •• Clear H2MAX AF +1.5 Mag | SB8620R15TM •• Gray H2MAX AF +1.5 Mag |
| SB8610R20 •• Clear +2.0 Mag | SB8620R20 •• Gray +2.0 Mag |
| SB8610R20TM •• Clear H2MAX AF +2.0 Mag | SB8620R20TM •• Gray H2MAX AF +2.0 Mag |
| SB8610R25 •• Clear +2.5 Mag | SB8620R25 •• Gray +2.5 Mag |
| SB8610R25TM •• Clear H2MAX AF +2.5 Mag | SB8620R25TM •• Gray H2MAX AF +2.5 Mag |
| SB8610R30 •• Clear +3.0 Mag | |
| SB8610R30TM •• Clear H2MAX AF +3.0 Mag | |



Ever-Lite®

General Specifications

Weight: 22 gm
 PD: 64 mm
 Bridge: 11.2 mm
 Lens base: 8 curve
 Lens size diagonal: 79.6 mm
 Lens size vertical: 43.3 mm
 Lens thickness: 1.8 mm
 Overall length (lens - tip): 163.5 mm
 Overall width (hinge - hinge): 134.3 mm
 Closest point between temple tips: 70 mm
 Closest point between lens: 11 mm

Materials

Lens: polycarbonate
 Frame: polycarbonate
 Temples: polycarbonate & thermoplastic elastomers (TPE)
 Hinge: polycarbonate
 Screw: stainless steel
 Nosepiece: thermoplastic rubbers (TPR)

Part No.	Lens Marking	Temple Marking
SB8610D	P + U6	P Z87 + / P c SEI Z94.3
SB8610DT	P + U6	P Z87 + / P c SEI Z94.3
SB8610DTM	P + U6 X	P Z87 + / P c SEI Z94.3
SB8620D	P + U6 L2.5	P Z87 + / P c SEI Z94.3
SB8620DT	P + U6 L2.5	P Z87 + / P c SEI Z94.3
SB8620DTM	P + U6 L2.5 X	P Z87 + / P c SEI Z94.3
SB8623D	P + S	P Z87 + / P c SEI Z94.3
SB8623DT	P + S	P Z87 + / P c SEI Z94.3
SB8624D	P + S	P Z87 + / P c SEI Z94.3
SB8625DTM	P + S X	P Z87 + / P c SEI Z94.3
SB8630D	P + U6	P Z87 + / P c SEI Z94.3
SB8660D	P + S	P Z87 + / P c SEI Z94.3
SB8660DT	P + S	P Z87 + / P c SEI Z94.3
SB8660DTM	P + S X	P Z87 + / P c SEI Z94.3
SB8665D	P + S	P Z87 + / P c SEI Z94.3
SB8680D	P + U6 L1.7	P Z87 + / P c SEI Z94.3
SB8680DT	P + U6 L1.7	P Z87 + / P c SEI Z94.3
SBL8610DTM	P + U6 X	P Z87 + / P c SEI Z94.3
SBL8620DTM	P + U6 L2.5 X	P Z87 + / P c SEI Z94.3

Lens Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 S: Special Purpose
 W: Welding filter
 X: Tested Anti-fog

UV Filter Transmittance

U6: .01% max effective far UV • .1% max near UV

Visible Light Filters

L1.7: 55% Max. Visible Light
 L2.5: 29% max visible light

Temple Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 c SEI Z94.3: CAN/CSA standard for eye and face protection devices

Ever-Lite Readers

General Specifications

Weight: 22 gm
 PD: 64 mm
 Bridge: 11.2 mm
 Lens base: 8 curve
 Lens size diagonal: 79.6 mm
 Lens size vertical: 43.3 mm
 Lens thickness: 1.8 mm
 Overall length (lens - tip): 163.5 mm
 Overall width (hinge - hinge): 134.3 mm
 Closest point between temple tips: 70 mm
 Closest point between lens: 11 mm

Materials

Lens: polycarbonate
 Frame: polycarbonate
 Temples: polycarbonate & thermoplastic elastomers (TPE)
 Hinge: polycarbonate
 Screw: stainless steel
 Nosepiece: thermoplastic rubbers (TPR)

Part No.	Lens Marking	Temple Marking
SB8610R15	P + U6	+1.50 P Z87 + / P c SEI Z94.3
SB8610R15TM	P + U6 X	+1.50 P Z87 + / P c SEI Z94.3
SB8610R20	P + U6	+2.00 P Z87 + / P c SEI Z94.3
SB8610R20TM	P + U6 X	+2.00 P Z87 + / P c SEI Z94.3
SB8610R25	P + U6	+2.50 P Z87 + / P c SEI Z94.3
SB8610R25TM	P + U6 X	+2.50 P Z87 + / P c SEI Z94.3
SB8610R30	P + U6	+3.00 P Z87 + / P c SEI Z94.3
SB8610R30TM	P + U6 X	+3.00 P Z87 + / P c SEI Z94.3
SB8620R15	P + U6 L2.5	+1.50 P Z87 + / P c SEI Z94.3
SB8620R15TM	P + U6 L2.5 X	+1.50 P Z87 + / P c SEI Z94.3
SB8620R20	P + U6 L2.5	+2.00 P Z87 + / P c SEI Z94.3
SB8620R20TM	P + U6 L2.5 X	+2.00 P Z87 + / P c SEI Z94.3
SB8620R25	P + U6 L2.5	+2.50 P Z87 + / P c SEI Z94.3
SB8620R25TM	P + U6 L2.5 X	+2.50 P Z87 + / P c SEI Z94.3

Lens Marking Symbols

P: Manufacturer's mark
 +: High impact
 S: Special purpose
 X: Tested Anti-fog

UV Filter Transmittance

U6: .01% max effective far UV • .1% max near UV

Visible Light Filters

L2.5: 29% max visible light

Temple Marking Symbols

+1.50: magnification of +1.5
 +2.00: magnification of +2.0
 +2.50: magnification of +2.5
 +3.00: magnification of +3.0

P: Manufacturer's mark

Z87: ANSI standard for eye and face protection devices

+ : High impact

c SEI Z94.3: CAN/CSA standard for eye and face protection devices