



Ever-Lite®

ANSI/ISEA Z87.1-2020 + | CAN/CSA Z94.3-2020 |
CE/UKCA EN 166

Soft nose piece for snug fit // Slim co-injected temples // Lightweight spectacle – 22 gm // Custom imprinting available



VARIATIONS

Black Frame | 21 Variations

SB8610D	Clear
SB8610DT	Clear H2X AF
SB8610DTM	Clear H2MAX AF
SB8614D	1.5 IR Filter
SB8620D	Gray
SB8620DT	Gray H2X AF
SB8620DTM	Gray H2MAX AF
SB8623D	Dark Gray
SB8623DT	Dark Gray H2X AF
SB8624D	Photochromic
SB8625DTM	Light Gray H2MAX AF

SB8630D	Amber
SB8650SF	5.0 IR Filter
SB8660D	Infinity Blue
SB8660DT	Infinity Blue H2X AF
SB8660DTM	Infinity Blue H2MAX AF
SB8660SF	3.0 IR Filter
SB86ARCS	Arc 1.5 IR Filter
SB8665D	Ice Blue Mirror
SB8680D	I/O Mirror
SB8680DT	I/O Mirror AF

Black and Lime Frame | 2 Variations

SBL8610DTM	Clear H2MAX AF
SBL8620DTM	Gray H2MAX AF

i Photochromic lenses change from clear to dark after exposure to direct UV light. Lenses change from dark to clear after removal from UV light.



**WATCH THE
EVER-LITE
VIDEO**

Ever-Lite® Readers

ANSI/ISEA Z87.1-2020 + | CAN/CSA Z94.3-2020

VARIATIONS

Black Frame | 7 Variations

SB8610R15TM	Clear H2MAX AF	+1.5 Mag
SB8610R20TM	Clear H2MAX AF	+2.0 Mag
SB8610R25TM	Clear H2MAX AF	+2.5 Mag
SB8610R30TM	Clear H2MAX AF	+3.0 Mag
SB8620R15TM	Gray H2MAX AF	+1.5 Mag
SB8620R20TM	Gray H2MAX AF	+2.0 Mag
SB8620R25TM	Gray H2MAX AF	+2.5 Mag





Ever-Lite®

General Specifications	Materials
Weight: 22 gm	Lens: Polycarbonate
PD: 64 mm	Frame: Polycarbonate
Bridge: 11.2 mm	Temples: Polycarbonate & Thermoplastic Elastomers (TPE)
Lens Base: 8 Curve	Hinge: Polycarbonate
Lens Size Diagonal: 79.6 mm	Screw: Stainless Steel
Lens Size Vertical: 43.3 mm	Nose Piece: Thermoplastic Rubbers (TPR)
Lens Thickness: 1.8 mm	
Overall Length (lens - tip): 163.5 mm	
Overall Width (hinge - hinge): 134.3 mm	
Closest Point Between Lens: 11 mm	

Part No.	Lens Marking	Temple Marking
SB8610D	P + U6	P Z87 + / P c SEI Z94.3
SB8610DT	P + U6	P Z87 + / P c SEI Z94.3
SB8610DTM	P + U6 X	P Z87 + / P c SEI Z94.3
SB8614D	P + R1.5 S	P Z87 +
SB8620D	P + U6 L2.5	P Z87 + / P c SEI Z94.3
SB8620DT	P + U6 L2.5	P Z87 + / P c SEI Z94.3
SB8620DTM	P + U6 L2.5 X	P Z87 + / P c SEI Z94.3
SB8623D	P + S	P Z87 + / P c SEI Z94.3
SB8623DT	P + S	P Z87 + / P c SEI Z94.3
SB8624D	P + S	P Z87 + / P c SEI Z94.3
SB8625DTM	P + S X	P Z87 + / P c SEI Z94.3
SB8630D	P + U6	P Z87 + / P c SEI Z94.3
SB8650SF	P + W5	P Z87 +
SB8660D	P + S	P Z87 + / P c SEI Z94.3
SB8660DT	P + S	P Z87 + / P c SEI Z94.3
SB8660DTM	P + S X	P Z87 + / P c SEI Z94.3
SB8660SF	P + W3	P Z87 +
SB86ARCS	P + R1.5 S	P Z87 +
SB8665D	P + S	P Z87 + / P c SEI Z94.3
SB8680D	P + U6 L1.7	P Z87 + / P c SEI Z94.3
SB8680DT	P + U6 L1.7	P Z87 + / P c SEI Z94.3
SBL8610DTM	P + U6 X	P Z87 + / P c SEI Z94.3
SBL8620DTM	P + U6 L2.5 X	P Z87 + / P c SEI Z94.3

Lens Marking Symbols	Temple Marking Symbols
P: Manufacturer's Mark	P: Manufacturer's Mark
Z87: ANSI/ISEA Standard for Eye and Face Protection Devices	Z87: ANSI/ISEA Standard for Eye and Face Protection Devices
+: High Impact	+: High Impact
S: Special Purpose	SE Z94.3: CAN/CSA Standard for Eye and Face Protection Devices
W: Welding Filter	
X: Tested Anti-Fog	
UV Filter Transmittance	
U6: .01% Max Effective Far UV • .1% Max Near UV	
Visible Light Filters	
L1.7: 55% Max. Visible Light	
L2.5: 29% Max. Visible Light	

Ever-Lite® Readers

General Specifications	Materials
Weight: 22 gm	Lens: Polycarbonate
PD: 64 mm	Frame: Polycarbonate
Bridge: 11.2 mm	Temples: Polycarbonate & Thermoplastic Elastomers (TPE)
Lens Base: 8 Curve	Hinge: Polycarbonate
Lens Size Diagonal: 79.6 mm	Screw: Stainless Steel
Lens Size Vertical: 43.3 mm	Nose Piece: Thermoplastic Rubbers (TPR)
Lens Thickness: 1.8 mm	
Overall Length (lens - tip): 163.5 mm	
Overall Width (hinge - hinge): 134.3 mm	
Closest Point Between Lens: 11 mm	

Part No.	Lens Marking	Temple Marking
SB8610R15TM	P + U6 X	+1.50 P Z87 + / P c SEI Z94.3
SB8610R20TM	P + U6 X	+2.00 P Z87 + / P c SEI Z94.3
SB8610R25TM	P + U6 X	+2.50 P Z87 + / P c SEI Z94.3
SB8610R30TM	P + U6 X	+3.00 P Z87 + / P c SEI Z94.3
SB8620R15TM	P + U6 L2.5 X	+1.50 P Z87 + / P c SEI Z94.3
SB8620R20TM	P + U6 L2.5 X	+2.00 P Z87 + / P c SEI Z94.3
SB8620R25TM	P + U6 L2.5 X	+2.50 P Z87 + / P c SEI Z94.3

Lens Marking Symbols	Temple Marking Symbols
P: Manufacturer's Mark	+1.50: Magnification of +1.5
+: High Impact	+2.00: Magnification of +2.0
S: Special Purpose	+2.50: Magnification of +2.5
X: Tested Anti-fog	+3.00: Magnification of +3.0
UV Filter Transmittance	P: Manufacturer's Mark
U6: .01% Max Effective Far UV • .1% Max Near UV	Z87: ANSI/ISEA Standard for Eye and Face Protection Devices
Visible Light Filters	+: High Impact
L2.5: 29% Max Visible Light	SE Z94.3: CAN/CSA Standard for Eye and Face Protection Devices

Product markings may vary // Updated as of 10.25