



Ever-Lite®

ANSI/ISEA Z87.1-2020 + | CAN/CSA Z94.3-2020 |
CE/UKCA EN 166

Soft nose piece for snug fit // Slim co-injected temples // Lightweight spectacle – 22 gm // Custom imprinting available



VARIATIONS

Black Frame | 17 Variations

SB8610D	Clear
SB8610DT	Clear H2X AF
SB8610DTM	Clear H2MAX AF
SB8620D	Gray
SB8620DT	Gray H2X AF
SB8620DTM	Gray H2MAX AF
SB8623D	Dark Gray
SB8623DT	Dark Gray H2X AF
SB8624D	Photochromic

SB8625DTM	Light Gray H2MAX AF
SB8630D	Amber
SB8660D	Infinity Blue
SB8660DT	Infinity Blue H2X AF
SB8660DTM	Infinity Blue H2MAX AF
SB8665D	Ice Blue Mirror
SB8680D	I/O Mirror
SB8680DT	I/O Mirror AF

Black and Lime Frame | 2 Variations

SBL8610DTM	Clear H2MAX AF
SBL8620DTM	Gray H2MAX AF

i Photochromic lenses change from clear to dark after exposure to direct UV light. Lenses change from dark to clear after removal from UV light.

Ever-Lite® Readers

ANSI/ISEA Z87.1-2020 + | CAN/CSA Z94.3-2020

VARIATIONS

Black Frame | 7 Variations

SB8610R15TM	Clear H2MAX AF	+1.5 Mag
SB8610R20TM	Clear H2MAX AF	+2.0 Mag
SB8610R25TM	Clear H2MAX AF	+2.5 Mag
SB8610R30TM	Clear H2MAX AF	+3.0 Mag
SB8620R15TM	Gray H2MAX AF	+1.5 Mag
SB8620R20TM	Gray H2MAX AF	+2.0 Mag
SB8620R25TM	Gray H2MAX AF	+2.5 Mag



**WATCH THE
EVER-LITE
VIDEO**



Ever-Lite®

General Specifications

Weight: 22 gm
PD: 64 mm
Bridge: 11.2 mm
Lens Base: 8 Curve
Lens Size Diagonal: 79.6 mm
Lens Size Vertical: 43.3 mm
Lens Thickness: 1.8 mm
Overall Length (lens - tip): 163.5 mm
Overall Width (hinge - hinge): 134.3 mm
Closest Point Between Lens: 11 mm

Materials

Lens: Polycarbonate
Frame: Polycarbonate
Temples: Polycarbonate & Thermoplastic Elastomers (TPE)
Hinge: Polycarbonate
Screw: Stainless Steel
Nose Piece: Thermoplastic Rubbers (TPR)

Part No.	Lens Marking	Temple Marking
SB8610D	P + U6	P Z87 + / P c SEI Z94.3
SB8610DT	P + U6	P Z87 + / P c SEI Z94.3
SB8610DTM	P + U6 X	P Z87 + / P c SEI Z94.3
SB8620D	P + U6 L2.5	P Z87 + / P c SEI Z94.3
SB8620DT	P + U6 L2.5	P Z87 + / P c SEI Z94.3
SB8620DTM	P + U6 L2.5 X	P Z87 + / P c SEI Z94.3
SB8623D	P + S	P Z87 + / P c SEI Z94.3
SB8623DT	P + S	P Z87 + / P c SEI Z94.3
SB8624D	P + S	P Z87 + / P c SEI Z94.3
SB8625DTM	P + S X	P Z87 + / P c SEI Z94.3
SB8630D	P + U6	P Z87 + / P c SEI Z94.3
SB8660D	P + S	P Z87 + / P c SEI Z94.3
SB8660DT	P + S	P Z87 + / P c SEI Z94.3
SB8660DTM	P + S X	P Z87 + / P c SEI Z94.3
SB8665D	P + S	P Z87 + / P c SEI Z94.3
SB8680D	P + U6 L1.7	P Z87 + / P c SEI Z94.3
SB8680DT	P + U6 L1.7	P Z87 + / P c SEI Z94.3
SBL8610DTM	P + U6 X	P Z87 + / P c SEI Z94.3
SBL8620DTM	P + U6 L2.5 X	P Z87 + / P c SEI Z94.3

Lens Marking Symbols

P: Manufacturer's Mark
Z87: ANSI/ISEA Standard for Eye and Face Protection Devices
+: High Impact
S: Special Purpose
W: Welding Filter
X: Tested Anti-Fog
UV Filter Transmittance
U6: .01% Max Effective Far UV •
.1% Max Near UV
Visible Light Filters
L1.7: 55% Max. Visible Light
L2.5: 29% Max. Visible Light

Temple Marking Symbols

P: Manufacturer's Mark
Z87: ANSI/ISEA Standard for Eye and Face Protection Devices
+: High Impact
SEI Z94.3: CAN/CSA Standard for Eye and Face Protection Devices

Ever-Lite® Readers

General Specifications

Weight: 22 gm
PD: 64 mm
Bridge: 11.2 mm
Lens Base: 8 Curve
Lens Size Diagonal: 79.6 mm
Lens Size Vertical: 43.3 mm
Lens Thickness: 1.8 mm
Overall Length (lens - tip): 163.5 mm
Overall Width (hinge - hinge): 134.3 mm
Closest Point Between Lens: 11 mm

Materials

Lens: Polycarbonate
Frame: Polycarbonate
Temples: Polycarbonate & Thermoplastic Elastomers (TPE)
Hinge: Polycarbonate
Screw: Stainless Steel
Nose Piece: Thermoplastic Rubbers (TPR)

Part No.	Lens Marking	Temple Marking
SB8610R15TM	P + U6 X	+1.50 P Z87 + / P c SEI Z94.3
SB8610R20TM	P + U6 X	+2.00 P Z87 + / P c SEI Z94.3
SB8610R25TM	P + U6 X	+2.50 P Z87 + / P c SEI Z94.3
SB8610R30TM	P + U6 X	+3.00 P Z87 + / P c SEI Z94.3
SB8620R15TM	P + U6 L2.5 X	+1.50 P Z87 + / P c SEI Z94.3
SB8620R20TM	P + U6 L2.5 X	+2.00 P Z87 + / P c SEI Z94.3
SB8620R25TM	P + U6 L2.5 X	+2.50 P Z87 + / P c SEI Z94.3

Lens Marking Symbols

P: Manufacturer's Mark
+: High Impact
S: Special Purpose
X: Tested Anti-fog
UV Filter Transmittance
U6: .01% Max Effective Far UV •
.1% Max Near UV
Visible Light Filters
L2.5: 29% Max Visible Light

Temple Marking Symbols

+1.50: Magnification of +1.5
+2.00: Magnification of +2.0
+2.50: Magnification of +2.5
+3.00: Magnification of +3.0
P: Manufacturer's Mark
Z87: ANSI/ISEA Standard for Eye and Face Protection Devices
+: High Impact
SEI Z94.3: CAN/CSA Standard for Eye and Face Protection Devices