

**Exeter®** ANSI • CE •

 RUBBER  
NOSEPIECE

 CO-INJECTED  
TEMPLES

 Built-in rubber nosepiece //  
 Co-injected rubber temples  
 // Extended lens // Custom  
 imprinting available

**Glossy Black Frame | 7 Variations**

- SB 5110DT •• Clear **H2X** AF
- SB 5120DT •• Gray **H2X** AF
- SB 5133DT • Shooter's Amber **H2X** AF
- SB 5155DT •• Sky Red Mirror AF
- SB 5170DT •• Silver Mirror AF
- SB 5175DT •• Blue Mirror AF
- SB 5180DT • I/O Mirror AF



Part No.	Lens Marking	Temple Marking
SB 5110DT	P Z87 + U6	P Z87 +
SB 5120DT	P Z87 + U6 L2.5	P Z87 +
SB 5133DT	P Z87 + S	P Z87 +
SB 5155DT	P Z87 + S	P Z87 +
SB 5170DT	P Z87 + S	P Z87 +
SB 5175DT	P Z87 + S	P Z87 +
SB 5180DT	P Z87 + U6 L1.7	P Z87 +

General Specifications
Weight: 29 gm
PD: 68 mm
Bridge: 13.4 mm
Lens base: 8 curve
Lens size diagonal: 70.8 mm
Lens size vertical: 44 mm
Lens thickness: 2.3 mm
Overall length (lens - tip): 157 mm
Overall width (hinge - hinge): 127.5 mm
Closest point between temple tips: 93 mm
Closest point between lens: 14.8 mm

Materials
Lens: polycarbonate
Frame: nylon
Temples: nylon + polyvinyl chloride (PVC)
Hinge: nylon
Screw: stainless steel
Nosepiece: polyvinyl chloride (PVC)

**Lens Marking Symbols**

P: Manufacturer's mark  
 Z87: ANSI standard for eye and face protection devices  
 +: High impact  
 S: Special Purpose

**UV Filter Transmittance**

U6: .01% max effective far UV • .1% max near UV

**Visible Light Filters**

L1.7: 55% Max. Visible Light  
 L2.5: 29% max visible light

**Temple Marking Symbols**

P: Manufacturer's mark  
 Z87: ANSI standard for eye and face protection devices  
 +: High impact  
 c SEI Z94.3: CAN/CSA standard for eye and face protection devices