PYRAMEX

DIELECTRIC | FOAM PADDED OPTIONS | RUBBER NOSE PIECE | RUBBER TIPS

H2X OPTIONS | H2MAX OPTIONS | INCLUDES STRAP | REMOVABLE TEMPLE STRAP

Fyxate™

ANSI/ISEA Z87.1-2020 + | CAN/CSA Z94.3-2020

Dielectric // Rubber temple tips and nose piece // Removable temple strap // Single wraparound lens // Flame resistant foam padding available on select options // Quick release strap available on foam padded options only



SB102

VARIATIONS

Black Temples | 5 Variations

SB10210S	Clear
SB10210ST	Clear H2X AF
SB10220S	Gray
SB10220ST	Gray H2X AF
SB10280S	I/O Mirror

Mirror lens option is not dielectric due to metal powder in lens coating.



Black Temples with Foam Padding | 3 Variations

SB10210STMFP	Clear H2MAX AF
SB10220STMFP	Gray H2MAX AF
SB10225STMFP	Light Gray H2MAX AF



Lime Temples with Foam Padding | 2 Variations

SBL10210STMFP	Clear H2MAX AF
SBL10220STMFP	Gray H2MAX AF

PYRAMEX

DIELECTRIC | FOAM PADDED OPTIONS | RUBBER NOSE PIECE | RUBBER TIPS

H2X OPTIONS | H2MAX OPTIONS | INCLUDES STRAP | REMOVABLE TEMPLE STRAP



SB10280S



SB10220STMFP

Part No.	Lens Marking	Temple Marking
SB10210S	P Z87 + U6	P Z87 + / P c SEI Z94.3
SB10210ST	P Z87 + U6	P Z87 + / P c SEI Z94.3
SB10220S	P Z87 + U6 L2.5	P Z87 + / P c SEI Z94.3
SB10220ST	P Z87 + U6 L2.5	P Z87 + / P c SEI Z94.3
SB10280S	P Z87 + U6 L1.7	P Z87 + / P c SEI Z94.3
SB10210STMFP	P Z87 + U6 X	P Z87 + / P c SEI Z94.3
SB10220STMFP	P Z87 + U6 L 2.5 X	P Z87 + / P c SEI Z94.3
SB10225STMFP	P Z87 + U6 L 2.5 X	P Z87 + / P c SEI Z94.3
SBL10210STMFP	P Z87 + U6 X	P Z87 + / P c SEI Z94.3
SBL10220STMFP	P Z87 + U6 L 2.5 X	P Z87 + / P c SEI Z94.3

General Specifications

Weight: 23.2 gm | 46.35 gm (with foam)

Bridge: 12.8 mm

Lens base: 9.5 curve

Lens size diagonal: 75.5 mm

Lens size vertical: 42.72 mm

Lens thickness: 1.95 mm

Overall length (lens - tip): 160.8 mm

Overall width (hinge - hinge): 129 mm

Materials

Lens: polycarbonate

Nosepiece: thermoplastic rubber (TPR)

Temples: polycarbonate & thermoplastic elastomers (TPE)

Temple tips: polyvinyl chloride (PVC)

Foam gasket: nylon and ethylene-vinyl acetate (EVA)

Strap: polyester

Lens Marking Symbols

P: Manufacturer's mark

Z87: ANSI standard for eye and face protection devices

+: High impact

S: Special Purpose

X: Tested Anti-fog

UV Filter Transmittance

U6: .01% max effective far UV • .1% max near UV

Visible Light Filters

L1.7: 55% Max. Visible Light

L2.5: 29% max visible light

Temple Marking Symbols

P: Manufacturer's mark

Z87: ANSI standard for eye and face protection devices

+: High impact

c SEI Z94.3: CAN/CSA standard for eye and face protection devices

Product markings may vary // Updated as of 11.26