EG304 | EG304T







Top Shelf Chemical Splash Goggle

Part	Lens	
EG304•••	Clear	
EG304T••••	Clear H2X Anti-Fog	

- Body tinted to reduce glare.
- Special one-way vent allows air to enter while keeping liquids out.
- Top shelf chemical splash goggle features generously sized heavy duty body and lens.
- Scratch resistant polycarbonate lens provides 99% UVA/B/C protection.

GENERAL SPECIFICATION		
Bridge: 42mm		
Lens Base: 4.25 curve		
Lens Size Diagonal: 150mm		
Lens Size Vertical: 76mm		
Lens Thickness: 2.2mm		
Overall Length (Lens-Tip): N/A		
Overall Width (Hinge-Hinge): 180mm		
PD: 68mm		
Weight: 68gm		

PACKAGING	
Polybag: 1pc	
Box: 12 pcs	
Case: 144 pcs	

EG304 | EG304T

COMPONENT	MATERIAL	FEATURES
Lens	Polycarbonate	Lens inset in PVC frame
Frame	PVC	Polyvinyl chloride, flexible fit
Nose Piece	PVC	Integral to frame
2 cap vents	LPDE	Also hold elastic band in place
Elastic Band	60% polyester 40% rubber thread	N/A

	PART	LENS	LENS MARKING	FRAME MARKING
Γ	EG304	Clear	2C- 1.2 P 1 B CE	CE P EN166 3 4 B
	EG304T	Clear H2X Anti-Fog	2C - 1.2 P 1 B N CE	CE P EN166 3 4 B

LENS MARKING

Code (field of use):

2 or 3: UV Filter 5 or 6: Solar Filter

Color Perception: C: Unimpaired color perception

Protection Class: 1.2 to 6: Degree of visible light filtration

Optical Class:

1: High optical quality / No optical distortion

Mechanical Strength:

S: Extra strong, resists a 22mm, 43g ball falling 1.30 m/s F: Low energy impact, resists a 6mm, 0.86g at 45 m/s B: Medium energy impact, resists a 6mm, 0.86g at 120 m/s A: High energy impact, resists a 6mm, 0.86g at 190 m/s

Symbols:

P: Manufacture Indication N: Filter with Anti-Fog features CE: European Standard

FRAME MARKING

Symbols:

CE: European Standard P: Manufacture Indication EN166: CE specification for protective eyewear

Mechanical Strength:

F: Low energy impact B: Medium energy impact BT: Medium energy impact at extreme temperatures

Protection Class:

3: Protection against liquid droplets4: Protection against large dust