

POLYURETHANE DIPPED















GL403C

HPPE | Polyurethane







ANSI/ISEA 105-2015 – CUT A2 | ABRASION 2 | PUNCTURE 3 EN388 – ABRASION 4 | CUT X | TEAR 4 | PUNCTURE 2 | CUT TDM-100 B

Polyurethane coating on the palm and fingers for good grip and precision handling // 13 gauge **PMXTECK** HPPE cut-resistant liner delivers cool comfort for all-day wear // Glove design offers excellent touch sensitivity and low particulate shed // Knit cuff creates a snug fit to keep out debris

Suggested Applications

Automotive // Cutting Applications // Glass Handling // Metal Work

Glove Breakdown

T	ype: Dipped Glove			
N	Material: Polyurethane			
L	Liner: 13 Gauge PMXTECK HPPE			
C	Cuff: HPPE + Latex Elastic			

⚠ WARNING: Cancer and Reproductive Harm −P65Warnings.ca.gov

This product contains components that may be a potential risk to allergic reactions (latex in the wrist cuff). Do not use in the event of hypersensitivity signs or a known allergy to latex.



REDEFINING COMFORT IN HAND PROTECTION



EXPERIENCE A NEW LEVEL OF PROTECTION AND COMFORT WITH PMXTECK.

Our unique plated knit technology for gloves creates an exterior built for durability and an interior so soft and smooth you'll forget you're wearing them.

With PMXTECK, comfort and safety go hand in hand.

Packaging

	Outer Polybag	Case	Made in China
GL403C	12 Pair	120 Pair	Made III Cilina

Product markings may vary // Updated as of 02.24

Glove Sizing

Small Medium	Large	X-Large	2X-Large
7 8	9	10	11

All sizes comply with EN ISO 21420 for comfort, fit and dexterity. Only wear the correct size for your hand. Gloves that are too loose or too tight will restrict movement and will not provide the optimal level of protection.