



POLYURETHANE DIPPED



GL406

Polyester | Polyurethane

ANSI/ISEA 105



EN388



3131X



ANSI/ISEA 105 – CUT A1 | ABRASION 3 | PUNCTURE 2
EN388 – ABRASION 3 | CUT 1 | TEAR 3 | PUNCTURE 1 | CUT TDM-100 X

Polyurethane palm coating // 13 gauge polyester liner // Touch sensitivity // Low particulate shed // Dark color hides stains

Suggested Applications

Electronics // General Duty // Parts Assembly //
Quality Control // Inspection // Construction

Glove Breakdown

Type: Dipped Glove
Material: Polyurethane
Liner: 13 Gauge Polyester
Cuff: Polyester + Latex

⚠ WARNING: Cancer and Reproductive Harm – P65Warnings.ca.gov
This product contains components that may be a potential risk to allergic reactions (latex in the wrist cuff). Do not use in the event of hypersensitivity signs or a known allergy to latex.

Packaging

	Outer Polybag	Case
GL406	12 Pair	120 Pair
Made in China		

Product markings may vary // Updated as of 12.25



Glove Sizing

GL406 XS – 2XL

X-Small 6	Small 7	Medium 8	Large 9	X-Large 10	2X-Large 11
--------------	------------	-------------	------------	---------------	----------------

All sizes comply with EN ISO 21420 for comfort, fit and dexterity. Only wear the correct size for your hand. Gloves that are too loose or too tight will restrict movement and will not provide the optimal level of protection.