



NITRILE DIPPED



Nitrile



Abrasion



Puncture



Tear

GL601DP

Nylon + Spandex | Nitrile |
Micro-Foam | Dotted Palm

ANSI/ISEA 105



EN388



4131X

ANSI/ISEA 105 – ABRASION 5 | PUNCTURE 2

EN388 – ABRASION 4 | CUT 1 | TEAR 3 | PUNCTURE 1 | CUT TDM-100 X

Micro-foam nitrile coating on palm and fingers offers an excellent grip on dry or wet surfaces by channeling liquids away // 15 gauge nylon/spandex liner is comfortable and breathable // Nitrile dots increase durability and grip // Reinforced thumb reduces stress in high-wear area // Glove design offers distinctive touch sensitivity // Knit cuff creates a snug fit to keep out debris

Suggested Applications

Automotive // General Assembly // General Duty //
Handling Oily Parts // Horticulture // Warehousing

Glove Breakdown

Type: Dipped Glove
Material: Micro-Foam Nitrile
Outer Liner: 15 Gauge Nylon + Spandex Liner
Cuff: Nylon + Latex Elastic
Dots: Nitrile Smooth

⚠ WARNING: Cancer and Reproductive Harm – P65Warnings.ca.gov

This product contains components that may be a potential risk to allergic reactions (latex in the wrist cuff). Do not use in the event of hypersensitivity signs or a known allergy to latex.



Packaging

	Outer Polybag	Case	Made in China
GL601DP	12 Pair	120 Pair	

Product markings may vary // Updated as of 06.23

Glove Sizing

X-Small	Small	Medium	Large	X-Large	2X-Large	3X-Large
6	7	8	9	10	11	12

All sizes comply with EN ISO 21420 for comfort, fit and dexterity. Only wear the correct size for your hand. Gloves that are too loose or too tight will restrict movement and will not provide the optimal level of protection.