



NITRILE DIPPED



Nitrile



Abrasion



Cut



Puncture



Tear

GL604C5

HPPE | Nitrile | Sandy

ANSI/ISEA 105



EN388



4X43D

ANSI/ISEA 105 – CUT A4 | ABRASION 6 | PUNCTURE 3
EN388 – ABRASION 4 | CUT X | TEAR 4 | PUNCTURE 3 | CUT TDM-100 D

Sandy nitrile coating on the palm and fingers provides an effective grip in dry and oily situations // 13 gauge HPPE cut-resistant liner delivers cool comfort for all-day wear // Knit cuff creates a snug fit to keep out debris

Suggested Applications

Aerospace // Assembly // Construction // Furniture
Manufacture // Handling Oily Parts // HVAC

Glove Breakdown

Type: Dipped Glove
Material: Nitrile Sandy
Outer Liner: 13 Gauge HPPE
Cuff: HPPE + Latex Elastic

This product contains components that may be a potential risk to allergic reactions (latex in the wrist cuff). Do not use in the event of hypersensitivity signs or a known allergy to latex.

Packaging

	Inner Polybag	Outer Polybag	Case
GL604C5	1 Pair	12 Pair	120 Pair
Made in China			

Product markings may vary // Updated as of 06.23



Glove Sizing

Small	Medium	Large	X-Large	2X-Large
7	8	9	10	11

All sizes comply with EN ISO 21420 for comfort, fit and dexterity. Only wear the correct size for your hand. Gloves that are too loose or too tight will restrict movement and will not provide the optimal level of protection.