

NITRILE DIPPED











GL604C5

HPPE | Nitrile | Sandy





C€ CK

ANSI/ISEA 105 – CUT A4 | ABRASION 6 | PUNCTURE 3 EN388 – ABRASION 4 | CUT X | TEAR 4 | PUNCTURE 3 | CUT TDM-100 D

Sandy nitrile coating on the palm and fingers provides an effective grip in dry and oily situations // 13 gauge HPPE cut-resistant liner delivers cool comfort for all-day wear // Knit cuff creates a snug fit to keep out debris

Suggested Applications

Aerospace // Assembly // Construction // Furniture Manufacture // Handling Oily Parts // HVAC

Glove Breakdown

Type: Dipped Glove
Material: Nitrile Sandy
Outer Liner: 13 Gauge HPPE
Cuff: HPPE + Latex Elastic

△ WARNING: Cancer and Reproductive Harm –P65Warnings.ca.gov This product contains components that may be a potential risk to allergic reactions (latex in the wrist cuff). Do not use in the event of hypersensitivity signs or a known allergy to latex.

Packaging

	Inner Polybag	Outer Polybag	Case		
GL604C5	1 Pair	12 Pair	120 Pair		
Made in China					

Product markings may vary // Updated as of 06.23



Glove Sizing

Small	Medium	Large	X-Large	2X-Large
7	8	9	10	11

All sizes comply with EN ISO 21420 for comfort, fit and dexterity. Only wear the correct size for your hand. Gloves that are too loose or too tight will restrict movement and will not provide the optimal level of protection.