



## NITRILE DIPPED



NITRILE



ABRASION



PUNCTURE



TEAR

# GL617

Nylon + Spandex | Nitrile | Micro-Foam

ANSI/ISEA 105



EN388



4131X

ANSI/ISEA 105 – CUT A1 | ABRASION 6 | PUNCTURE 2

EN388 – ABRASION 4 | CUT 1 | TEAR 3 | PUNCTURE 1 | CUT TDM-100 X

Micro-foam nitrile three-quarter dipped coating offers an excellent grip on dry or wet surfaces by channeling liquids away // 15 gauge nylon/spandex liner is comfortable and breathable // Glove design offers distinctive touch sensitivity // Knit cuff creates a snug fit to keep out debris

## Suggested Applications

Automotive // General Assembly // General Duty Purpose // Handling Oily Parts // Horticulture // Warehousing

## Glove Breakdown

Type: Dipped Glove
Material: Nitrile Micro-Foam
Outer Liner: 15 Gauge Nylon + Spandex
Cuff: Nylon + Latex Elastic

⚠ WARNING: Cancer and Reproductive Harm – P65Warnings.ca.gov

This product contains components that may be a potential risk to allergic reactions (latex in the wrist cuff). Do not use in the event of hypersensitivity signs or a known allergy to latex.

## Packaging

	Outer Polybag	Case
GL617	12 Pair	120 Pair
Made in China		

Product markings may vary // Updated as of 10.25



## Glove Sizing

Small 7	Medium 8	Large 9	X-Large 10	2X-Large 11
------------	-------------	------------	---------------	----------------

All sizes comply with EN ISO 21420 for comfort, fit and dexterity. Only wear the correct size for your hand. Gloves that are too loose or too tight will restrict movement and will not provide the optimal level of protection.