



Goliath® ANSI • CE • UKCA • CSA •



CO-INJECTED
TEMPLES



POLARIZED
OPTION

Co-injected rubber
temples

Black Frame | 6 Variations

- ESB5610D Clear
- ESB5620D Gray
- ESB5620DT Gray **H2X AF**
- ESB5621D **Polarized** Gray
- ESB5665D Ice Blue Mirror
- ESB5665DT Ice Blue Mirror AF

White Frame | 2 Variations

- SW5620D Gray
- SW5665D Ice Blue Mirror



SW56

Part No.	Lens Markings	Frame Markings	General Specifications	Materials
ESB5610D	2C-1.2 P 1F CE	CE P EN166 F UKCA	Weight: 35 gm	Lens: polycarbonate
ESB5620D	5-2.5 P 1F CE	CE P EN166 F UKCA	PD: 68 mm	Temples: polycarbonate & thermoplastic rubbers
ESB5620DT	5-2.5 P 1F N CE	CE P EN166 F UKCA	Bridge: 13.8 mm	Hinge: polycarbonate
ESB5621D	5-3.1 P 1F CE	CE P EN166 F UKCA	Lens base: 8 curve	Screw: stainless steel
ESB5665D	5-3.1 P 1F CE	CE P EN166 F UKCA	Lens size diagonal: 62.6 mm	Side shields: polycarbonate
ESB5665DT	5-3.1 P 1F N CE	CE P EN166 F UKCA	Lens size vertical: 37.6 mm	
ESW5620D	5-2.5 P 1F CE	CE P EN166 F UKCA	Lens thickness: 2.3 mm	
ESW5655D	5-3.1 P 1F CE	CE P EN166 F UKCA	Overall length (lens - tip): 163.5 mm	
			Overall width (hinge - hinge): 131 mm	
			Closest point between temple tips: 96.5 mm	
			Closest point between lens: 18 mm	

Lens Marking Symbols

Code - field of use

2 or 3: UV filter

5 or 6: Solar filter

Colour Perception

C: Unimpaired colour perception

Protection Class

1.2 - 6: Degree of visible light filtration

Optical Class

1: High optical quality - no optical distortion

Mechanical Strength

F: Low energy impact, resists a 6 mm, .86 g at 45 m/s

Symbols

P: Manufacturer's mark

N: Filter with anti-fog

CE: Certification of the European Union

Temple Marking Symbols

Symbols

CE: Certification for European Union

P: Manufacturer's mark

EN166: Standard for protective eyewear

UKCA: Certification for United Kingdom

Mechanical Strength

F: Low energy impact