

Goliath®

ANSI/ISEA Z87.1-2020 + | CAN/CSA Z94.3-2020 | CE/UKCA EN 166

Co-injected rubber temples //
Custom imprinting available

VARIATIONS

Black Frame | 7 Variations

-  SB5610D Clear
-  SB5620D Gray
-  SB5620DT Gray **H2X AF**
-  SB5621D **Polarized** Gray
-  SB5645D Ice Orange Mirror
-  SB5665D Ice Blue Mirror
-  SB5670D Silver Mirror

White Frame | 2 Variations

-  SW5655D Clear
-  SW5665D Clear **H2X AF**



SW56

Part No.	Lens Markings	Frame Markings	General Specifications	Materials
SB5610D	P + U6	P Z87 + / P c SEI Z94.3	Weight: 35 gm	Lens: polycarbonate
SB5620D	P + U6 L2.5	P Z87 + / P c SEI Z94.3	PD: 68 mm	Temples: polycarbonate & thermoplastic rubbers
SB5620DT	P + U6 L2.5	P Z87 + / P c SEI Z94.3	Bridge: 13.8 mm	Hinge: polycarbonate
SB5621D	P + S	P Z87 + / P c SEI Z94.3	Lens base: 8 curve	Screw: stainless steel
SB5645D	P + S	P Z87 + / P c SEI Z94.3	Lens size diagonal: 62.6 mm	Side shields: polycarbonate
SB5645D	P + S	P Z87 + / P c SEI Z94.3	Lens size vertical: 37.6 mm	
SB5665D	P + S	P Z87 + / P c SEI Z94.3	Lens thickness: 2.3 mm	
SB5670D	P + S	P Z87 + / P c SEI Z94.3	Overall length (lens - tip): 163.5 mm	
SW5655D	P + S	P Z87 + / P c SEI Z94.3	Overall width (hinge - hinge): 131 mm	
SW5665D	P + S	P Z87 + / P c SEI Z94.3	Closest point between lens: 18 mm	

Lens Marking Symbols

P: Manufacturer's mark

+: High impact

S: Special Purpose

UV Filter Transmittance

U6: .01% max effective far UV • .1% max near UV

Visible Light Filters

L1.7: 55% Max. Visible Light

L2.5: 29% max visible light

Temple Marking Symbols

P: Manufacturer's mark

Z87: ANSI standard for eye and face protection devices

+: High impact

c SEI Z94.3: CAN/CSA standard for eye and face protection devices