PYRAMEX

FOAM PADDING | INCLUDES STRAP | BALLISTIC | VENTED FRAME | REMOVABLE TEMPLE STRAP

Highlander Plus™

ANSI/ISEA Z87.1-2020+ | CAN/CSA Z94.3-20 | CE/UKCA EN166 | MIL-PRF-32432

Removable indirect vented flame resistant foam carriage // Removable temple strap // Fully adjustable elastic strap with quick release attaches to temples providing a secure fit // Scratch resistant polycarbonate lens provides 99% UVA/B/C protection // Passes MIL-PRF-32432 High Velocity Impact Standards



VARIATIONS

Black-Gray Body with Strap | 5 Variations

SBG5010DT	Clear H2X AF
SBG5020DT	Gray H2X AF
SBG5030DT	Amber H2X AF
SBG5055DT	Sky Red Mirror AF
SBG5080DT	I/O Mirror AF

Highlander Plus is partially foam padded which allows for airflow.

Part No.	Lens Marking	Temple Marking
SBG5010DT	P + U6	P Z87 + / P c SEI Z94.3
SBG5020DT	P + U6 L2.5	P Z87 + / P c SEI Z94.3
SBG5030DT	P + U6	P Z87 + / P c SEI Z94.3
SBG5055DT	P + S	P Z87 + / P c SEI Z94.3
SBG5080DT	P + U6 L1.7	P Z87 + / P c SEI Z94.3

General Specifications	Materials
Weight: 36 gm	Lens: Polycarbonate
PD: 68 mm	Nose Piece: Polyvinyl Chloride (PVC)
Bridge: 9 mm	Temples: Nylon
Lens Base: 8 curve	Foam: Chloroprene Rubber (CR)
Lens Size Diagonal: 68.4 mm	Strap: Polyester
Lens Size Vertical: 49 mm	Screw: Stainless Steel
Lens Thickness: 2.3 mm	
Overall Length (lens-tip): 166 mm	
Overall Width (hinge-hinge): 136.5 mm	
Closest Point Between Lens: 15.6 mm	

Lens Marking Symbols

P: Manufacturer's Mark

+: High Impact

S: Special Purpose

UV Filter Transmittance

U6: .01% Max Effective Far UV • .1% Max Near UV

Visible Light Filters

L1.7: 55% Max. Visible Light

L2.5: 29% Max Visible Light

Symbols

P: Manufacturer's Mark

N: Filter with Anti-Fog

CE: Europe Standard

B: Medium Energy Impact, Resists a 6mm, 0.86g at 120 m/s

A: High Energy Impact, Resists a 6mm, 0.86g at 190 m/s

Temple Marking Symbols

Symbols

P: Manufacturer's Mark

Z87: ANSI Standard for Eye and Face Protection Devices

+: High Impact

c SEI Z94.3: CAN/CSA Standard for Eye and Face Protection Devices

Product markings may vary // Updated as of 11.26