



SEALED



Highlander Plus™

ANSI • CE/UKCA • CSA • Ballistic •

Removable indirect vented flame resistant foam carriage // Detachable strap // Fully adjustable elastic strap with quick release attaches to temples providing a secure fit // Scratch resistant polycarbonate lens provides 99% UVA/B/C protection // Passes MIL-PRF-32432 High Velocity Impact Standards



Black-Grey Body with Strap | 5 Variations

- SBG5010DT ●●● Clear **H2X** AF
- SBG5020DT ●●● Gray **H2X** AF
- SBG5030DT ●●● Amber **H2X** AF
- SBG5055DT ●●● Sky Red Mirror AF
- SBG5080DT ● ● ● I/O Mirror AF

Part No.	Lens Marking	Temple Marking	Lens Marking Symbols	Temple Marking Symbols	Measurements
SBG5010DT	P + U6	P Z87 + / P c SEI Z94.3	P: Manufacturer's mark	Symbols	Weight: 36 gm
SBG5020DT	P + U6 L2.5	P Z87 + / P c SEI Z94.3	+ : High impact	P: Manufacturer's mark	PD: 68 mm
SBG5030DT	P + U6	P Z87 + / P c SEI Z94.3	S: Special Purpose	Z87: ANSI standard for eye and face protection devices	Bridge: 9 mm
SBG5055DT	P + S	P Z87 + / P c SEI Z94.3	UV Filter Transmittance	+ : High impact	Lens base: 8 curve
SBG5080DT	P + U6 L1.7	P Z87 + / P c SEI Z94.3	U6: .01% max effective far UV • .1%	c SEI Z94.3: CAN/CSA standard for eye and face protection devices	Lens size diagonal: 68.4 mm

Materials

Lens: Polycarbonate
Nosepiece: Polyvinyl Chloride (PVC)
Foam: Chloroprene Rubber (CR)
Frame: Nylon
Temples: Nylon
Strap: Polyester
Screw: Stainless Steel

Visible Light Filters

- L1.7: 55% Max. Visible Light
- L2.5: 29% max visible light

Symbols

- P: Manufacturer's mark
- N: Filter with anti-fog
- CE: Europe standard
- B: Medium energy impact, resists a 6mm, 0.86g at 120 m/s
- A: High energy impact, resists a 6mm, 0.86g at 190 m/s

- Overall length (lens - tip): 166 mm
- Overall width (hinge - hinge): 136.5 mm
- Closest point between temple tips: 80 mm
- Closest point between lens: 15.6 mm

i Highlander Plus is partially foam padded which allows for airflow.