

Integra®

ANSI/ISEA Z87.1-2020 + | CAN/CSA Z94.3-2020

Adjustable temples ensure reliable performance // Custom imprinting available



VARIATIONS

Black Frame | 3 Variations

-  SB410S Clear
-  SB410ST Clear AF
-  SB420S Gray



Red, White, & Blue Frame | 1 Variation

-  SNWR410S Clear



Red Frame | 1 Variation

-  SR410S Clear



Blue Frame | 1 Variation

-  SN410S Clear

Part No.	Lens Marking	Temple Marking
SB410S	P + U6	P Z87 + / P c SEI Z94.3
SB410ST	P + U6	P Z87 + / P c SEI Z94.3
SB420S	P + U6 L3	P Z87 + / P c SEI Z94.3
SN410S	P + U6	P Z87 + / P c SEI Z94.3
SNWR410S	P + U6	P Z87 + / P c SEI Z94.3
SR410S	P + U6	P Z87 + / P c SEI Z94.3

General Specifications

Weight: 35 gm
 PD: 68 mm
 Lens Base: 4 curve
 Lens Size Diagonal: 138 mm
 Lens Size Vertical: 39 mm
 Lens Thickness: 2.0 mm
 Overall Length (lens - tip): 85 mm
 Overall Width (hinge - hinge): 149 mm

Materials

Lens: Polycarbonate
 Side Shield: Polycarbonate
 Frame: Nylon 66
 Temples: Nylon 66
 Hinge: Polycarbonate
 Screw: Nickel Plated
 Nose Piece: Polycarbonate

Lens Marking Symbols

P: Manufacturer's Mark
 Z87: ANSI Standard for Eye and Face Protection Devices
 +: High Impact
 S: Special Purpose
 W3: IR3 Lens
 W5: IR5 Lens

UV Filter Transmittance

U6: .01% Max Effective Far UV •
 .1% Max Near UV

Visible Light Filters

L3: 18% Max. Visible Light

Temple Marking Symbols

P: Manufacturer's Mark
 Z87: ANSI Standard for Eye and Face Protection Devices
 +: High Impact
 Z94.3: CAN/CSA Standard for Eye and Face Protection Devices

Product markings may vary // Updated as of 10.25