PYRAMEX

H2MAX OPTIONS | BALLISTIC | DIELECTRIC | PASSES D3 DROPLET AND SPLASH TEST | PASSES D4 DUST TEST | RUBBER TIPS

REMOVABLE TEMPLE STRAP | RUBBER NOSE PIECE | INTERCHANGE TEMPLE/STRAP | INCLUDES STRAP | ADJUSTABLE TEMPLES

Isotope™

ANSI/ISEA Z87.1-2020 + | CAN/CSA Z94.3-2020 | CE/UKCA EN 166 | MIL-PRF-32432

Dielectric // Interchangeable temples and neoprene strap // Removable, adjustable temple strap // Rubber temple tips adjust to three different lengths // Frame features a rubber gasket // Passes Ballistic MIL-PRF-32432 High Velocity Impact standards when worn with strap // Passes D3: Droplet and Splash Test when worn with temples/temples and temple strap/ interchangeable strap // Passes D4: Dust Test when worn with temples/temples and temple strap/ interchangeable strap // Custom imprinting available



VARIATIONS

Black Frame | 3 Variations

- GB9410STM — Clear **H2MAX** AF
- GB9420STM — Gray **H2MAX** AF
- GB9430STM — Amber **H2MAX** AF

Part No.	Lens Marking	Frame Marking
GB9410STM	P Z87 + U6 X	P Z87 + D3 D4 / P c SEI Z94.3
GB9420STM	P Z87 + U6 L2.5 X	P Z87 + D3 D4 / P c SEI Z94.3
GB9430STM	P Z87 + U6 X	P Z87 + D3 D4 / P c SEI Z94.3

Lens Marking Symbols

P: Manufacturer's Mark

Z87: ANSI Standard for Eye and Face Protection Devices

+: High Impact

X: Tested Anti-Fog

UV Filter Transmittance

U6: .01% Max Effective Far UV • .1% Max Near UV

Visible Light Filters

L1.7: 55% Max. Visible Light

L2.5: 29% Max. Visible Light

Frame Marking Symbols

P: Manufacturer's Mark

Z87: ANSI Standard for Eye and Face Protection Devices

+: High Impact

D3: Droplet & Splash Test with Strap

D4: Dust Test

c SEI Z94.3: CAN/CSA Standard for Eye and Face Protection Devices

General Specifications

Weight: 41 gm Spectacle | 40.68 gm Goggle

PD: 64 mm

Bridge: 11.7 mm

Lens Base: 9.5 curve

Lens Size Diagonal: 74.7 mm

Lens Size Vertical: 45 mm

Lens Thickness: 2.3 mm

Overall Length (lens - tip): 163 - 173 mm Spectacle | 73 mm Goggle

Overall Width (hinge - hinge): 134 mm

Closest Point Between Strap Holding Parts: 137 mm

Closest Point Between Lens: 13 mm

Strap Length: 192 mm Spectacle | 520 mm Goggle

Materials

Lens: Polycarbonate

Frame: Polycarbonate

Gasket: Polycarbonate and Thermoplastic Elastomers (TPE)

Temple: Polycarbonate

Temple Tips: Polycarbonate and Thermoplastic Elastomers (TPE)

Temple Strap: Polyester

Goggle Strap: Neoprene

Goggle Strap Holder: Polycarbonate

Strap Takeup Loop: Nylon

Sleeve: Polycarbonate

Nose Piece: Thermoplastic Rubbers (TPR)

WATCH THE **ISOTOPE** VIDEO

Product markings may vary // Updated as of 11.26