

## Provoq® ANSI • CSA •



Soft nosepiece // Rubber temples //  
Custom imprinting available

### Black Temples | 9 Variations

- S7210S ●● Clear
- S7210ST ●● Clear AF
- S7220S ●● Gray
- S7220ST ●● Gray AF
- S7230S ●● Amber
- S7260S ●● Infinity Blue
- S7270S ●● Silver Mirror
- S7275S ●● Blue Mirror
- S7280S ●● I/O Mirror

### Pink Temples | 1 Variation

- SP7210ST ●● Clear AF



SP72

| Part No. | Lens Markings   | Frame Markings          | General Specifications                      | Materials                        |
|----------|-----------------|-------------------------|---|----------------------------------|
| S7210S   | P Z87 + U6      | P Z87 + / P c SEI Z94.3 | Weight: 24.9 gm                             | Lens: polycarbonate              |
| S7210ST  | P Z87 + U6      | P Z87 + / P c SEI Z94.3 | PD: 64 mm                                   | Temples: polycarbonate           |
| S7220S   | P Z87 + U6 L3   | P Z87 + / P c SEI Z94.3 | Bridge: 16.66 mm                            | Hinge: polycarbonate             |
| S7220ST  | P Z87 + U6 L3   | P Z87 + / P c SEI Z94.3 | Lens base: 9 curve                          | Screw: plated steel              |
| S7230S   | P Z87 + S       | P Z87 + / P c SEI Z94.3 | Lens size diagonal: 79.83 mm                | Temple Tip: thermoplastic rubber |
| S7260S   | P Z87 + S       | P Z87 + / P c SEI Z94.3 | Lens size vertical: 41.12 mm                | Nosepiece: thermoplastic rubber  |
| S7270S   | P Z87 + S       | P Z87 + / P c SEI Z94.3 | Lens thickness: 2.4 mm                      |                                  |
| S7275S   | P Z87 + S       | P Z87 + / P c SEI Z94.3 | Overall length (lens - tip): 158 mm         |                                  |
| S7280S   | P Z87 + U6 L1.7 | P Z87 + / P c SEI Z94.3 | Overall width (hinge - hinge): 136 mm       |                                  |
| SP7210ST | P Z87 + U6      | P Z87 + / P c SEI Z94.3 | Closest point between temple tips: 79.35 mm |                                  |
|          |                 |                         | Closest point between lens: 8.18 mm         |                                  |

### Lens Marking Symbols

P: Manufacturer's mark  
Z87: ANSI standard for eye and face protection devices  
+: High impact  
S: Special Purpose  
UV Filter Transmittance  
U6: .01% max effective far UV • .1% max near UV

### Visible Light Filters

L1.7: 55% max visible light  
L3: 18% max visible light

### Temple Marking Symbols

P: Manufacturer's mark  
Z87: ANSI standard for eye and face protection devices  
+: High impact  
c SEI Z94.3: CAN/CSA standard for eye and face protection devices