

Provoq®

ANSI/ISEA Z87.1-2020 + | CAN/CSA Z94.3-2020

Soft nose piece provides comfort for extended use //

Rubber temple tips // Custom imprinting available

VARIATIONS

Black Temples | 9 Variations

	S7210S	Clear
	S7210ST	Clear AF
	S7220S	Gray
	S7220ST	Gray AF
	S7230S	Amber
	S7260S	Infinity Blue
	S7270S	Silver Mirror
	S7275S	Blue Mirror
	S7280S	I/O Mirror



Part No.	Lens Markings	Frame Markings	General Specifications	Materials
S7210S	P Z87 + U6	P Z87 + / P c SEI Z94.3	Weight: 24.9 gm	Lens: Polycarbonate
S7210ST	P Z87 + U6	P Z87 + / P c SEI Z94.3	PD: 64 mm	Temples: Polycarbonate
S7220S	P Z87 + U6 L3	P Z87 + / P c SEI Z94.3	Bridge: 16.66 mm	Hinge: Polycarbonate
S7220ST	P Z87 + U6 L3	P Z87 + / P c SEI Z94.3	Lens Base: 9 curve	Screw: Plated Steel
S7230S	P Z87 + S	P Z87 + / P c SEI Z94.3	Lens Size Diagonal: 79.83 mm	Temple Tip: Thermoplastic Rubber
S7260S	P Z87 + S	P Z87 + / P c SEI Z94.3	Lens Size Vertical: 41.12 mm	Nose Piece: Thermoplastic Rubber
S7270S	P Z87 + S	P Z87 + / P c SEI Z94.3	Lens Thickness: 2.4 mm	
S7275S	P Z87 + S	P Z87 + / P c SEI Z94.3	Overall Length (lens - tip): 158 mm	
S7280S	P Z87 + U6 L1.7	P Z87 + / P c SEI Z94.3	Overall Width (hinge - hinge): 136 mm	
			Closest Point Between Lens: 8.18 mm	

Lens Marking Symbols

P: Manufacturer's Mark

Z87: ANSI Standard for Eye and Face Protection Devices

+: High Impact

S: Special Purpose

UV Filter Transmittance

U6: .01% Max Effective Far UV • .1% Max Near UV

Visible Light Filters

L1.7: 55% Max Visible Light

L3: 18% Max Visible Light

Temple Marking Symbols

P: Manufacturer's Mark

Z87: ANSI Standard for Eye and Face Protection Devices

+: High Impact

 Z94.3: CAN/CSA Standard for Eye and Face Protection Devices

Product markings may vary // Updated as of 10.25