



PYRAMEX
Perform At Your Peak

RPD3001 Series **ANSI CE**

Metal Detectable Reusable Corded Earplugs

NRR 25dB SNR 30dB



REUSABLE
EARPLUG

Three flexible rubber flanges form a secure seal

Reusable corded earplugs embedded with metal shavings in the plug and cord for metal and magnetic detectability and can be cleaned with soap and water

Part No.

RPD3001 ●●

General Specifications

Noise reduction rating (NRR): 25dB

Single number rating (SNR): 30dB

Hearing protection style: corded plug

Resusable: yes

Metal detectable: yes

Size: one size fits most

Plug color: blue

Plug dimension: 2.6 x 1.2 cm

Cord color: blue

Cord length: 75 cm

Materials

Plug: thermoplastic rubber (TPR)

Cord: polyvinyl chloride (PVC) with embedded metal shavings

Product Guidelines

The level of noise entering a person's ear, when hearing protection is worn as directed is approximated by the difference between the A-weighted environmental level and the NRR.

Example: 1. The environmental noise level at the ear is 92 dB(A).

2. The NRR is 32 decibels (dB).

3. The level of noise entering the ear is approximately equal to 60 dB(A).

CAUTION: For noise environments dominated by frequencies below 500 Hz, the C-weighted environmental noise level should be used. Improper fit of this device will reduce its effectiveness in continuous noise. Plugs should be inserted with a gentle rocking; twisting motion while opposite hand is opening ear canal by pulling the top of ear. Although hearing protectors can be recommended for protection against the harmful effects of impulse noise, the Noise Reduction Rating (NRR) is based on the attenuation noise and may not be an accurate indicator of the protection attainable against impulsive noise, such as gunfire.



There's more to see at
PYRAMEXSAFETY.COM

(P) +44 (0) 1635 254220 | (E) info@pyramexeurope.com

All hearing protection meets ANSI S3.19 standards (●). Some options meet European (CE EN-352:2002) (●) standards. For more information visit our website or contact your sales representative.