

RIDGELINE[®] CAP STYLE

SIGNATURE STYLE, PROVEN PROTECTION

Discover the ultimate in head protection with the Ridgeline[®] Cap Style hard hat. Its ABS shell delivers superior impact resistance and lightweight comfort, while the low-profile design ensures a modern, comfortable fit. The adjustable 4-point ratchet suspension fits sizes 6.5 to 8 securely.



DURABLE
ABS SHELL



RATCHET
SUSPENSION



ABS SHELL

HP44110C

SIDE SHIELD
PROTECTION

SWINGING RATCHET
SUSPENSION


FEATURES

Robust, Lightweight Shell: ABS shell ensures durable, lightweight protection

Effortless Adjustment: 4-point swinging ratchet suspension easily adjusts to provide a perfect fit across all head sizes

Low-Profile Design: Designed to ensure a modern and more comfortable fit








Hygienic Solution: Replaceable sweatband promotes cleanliness and comfort

Engineered Toughness: Meets ANSI/ISEA Z89.1-2014 Type I,  certified for CAN/CSA Z94.1-2015 Type I (with side shield clip only) to ensure durability and confidence in performance



LEARN MORE

ABOUT THE RIDGELINE
CAP STYLE KEY FEATURES

PYRAMEX[®]       

P 800.736.8673 // F 901.861.4967 // W PYRAMEX.COM

RIDGELINE[®] CAP STYLE

SIGNATURE STYLE, PROVEN PROTECTION

Discover the ultimate in head protection with the Ridgeline[®] Cap Style hard hat. Its ABS shell delivers superior impact resistance and lightweight comfort, while the low-profile design ensures a modern, comfortable fit. The adjustable 4-point ratchet suspension fits sizes 6.5 to 8 securely.



VARIATIONS

NON-VENTED

4-Point Ratchet Suspension | 6 Variations

- HP44110C White
- HP44116C Matte White Graphite Pattern
- HP44117C Matte Black Graphite Pattern
- HP44130C Yellow
- HP44131C Hi-Vis Lime
- HP44165C Dark Blue




i Ridgeline Cap Style must be worn with side shield clip to meet CAN/CSA Z94.1

MATERIALS

Shell: ABS (Acrylonitrile Butadiene Styrene) Plastic
Sweatband: Polyester + Polyurethane (PU) Foam
Suspension: HDPE (Polypropylene) + High Impact Nylon

⚠ WARNING: Cancer and Reproductive Harm – P65Warnings.ca.gov

MARKINGS

Standard: ANSI/ISEA Z89.1-2014 + CAN/CSA Z94.1-2015 (with side shield clip only)
Type: Type I Cap Style Hard Hat
Class: Non-Vented – Class E (Electrical) Rated for 20,000 Volts,
LT: Low Temperatures Protection up to -22°F HT: High Temperatures Protection up to 140°F
HV: Meets All Requirements for High-Visibility (HP44131C)
Reverse Donning:  Indicates Approval for Assembling the Suspension In the Reverse Direction for Reverse Wearing
Date Code: Indicates Month and Year Shell Was Molded - Does Not Indicate Service Life.

Product markings may vary // Updated as of 11.25



HP6PTSUS – Transforms 4-point suspensions to 6-point for cap style and full brim hard hats



REPLACEMENT PARTS



HPR441 – 4-point ratchet suspension



HPRBANDR – Ridgeline cap style and full brim hard hat sweat suspension

GENERAL SPECIFICATIONS

Weight: 358 gm
Shell Thickness: 2-4 mm
Dimensions: 28" x 22" x 15.2" cm
Suspension Adjust Sizing: 6.5 to 8
Suspension: Adjustable with Ratcheting Wheel

PRODUCT GUIDELINES

Never alter or modify the shell or suspension system. Always use original replacement parts. Decals/stickers are acceptable if they do not affect a hard hat's protective rating or make it difficult to find damage.

Inspect your hard hat shell and suspension on a regular basis. Check for cracks or faulty parts each time it is to be used. If you notice any sign of damage, the faulty part should be discarded and immediately replaced. Inspect the hard hat each time before use and replace immediately if there is any sign of damage.

The service life of a hard hat begins when the hard hat is put into service. Maximum service life is 5 years for the shell and 1 year for the suspension, beginning immediately upon first use. If the hard hat has received a considerable strike, it should be replaced immediately, even if there is no visible damage. Only use genuine Pyramex accessories and replacement parts that have been approved for use with this helmet.

Clean only with mild soap and lukewarm water. DO NOT USE paints, chemicals, gasoline, or similar substances on the hard hat. If these substances are applied on the shell, its impact resistance and other features could be decreased and could be dangerous for the user.

Store hard hat in a cool place out of direct sunlight. Do not store in vehicles where the interior temperature can become extreme and cause deterioration of the hard hat.