



SL Series Sleek Shell

Ideal for linemen
Polyethylene materials
Seamless low profile design
4-point ratchet suspension
No rain trough
Soft brow pad
Options meet Class E, G, and C

Custom imprinting available

Cap Style		Full Brim		
4-Point Ratchet	5 Variations	4-Point Ratchet	5 Variations	
HPS14110 •	White	HPS24110 •	White	
HPS14112 •	Gray	HPS24112 •	Gray	

HPSSUS Replacement Suspension Only



SL Series Sleek Shell head protection meets ANSI Z89.1 (\bullet), Type 1, Class C, G and E. For specific options visit our website or contact your sales representative.





Cap Style

General Specifications

Weight: 408 gm Dimensions: 14 cm x 28 cm x 21 cm Suspensions: 4-point ratchet Suspension adjust sizing: 55-62cm (6 7/8"-7 ¾") Standards: ANSI/ISEA Z89.1-2014 Types: Type 1 Classes: Class E, G, and C

Full Brim

General Specifications

Weight: 386 gm Dimensions: 16.5 cm x 31 cm x 26.7 cm Suspensions: 4-point ratchet Suspension adjust sizing: 55-62 cm (6 7/8"-7 ¾") Standards: ANSI/ISEA Z89.1-2014 Types: Type 1 Classes: Class E, G, and C

Materials

Shell: high density polyethylene Suspension: nylon

Markings

Types: Type 1 offers protection to the top of the head

Classes: Class E (electrical) rated for 20,000 volts | Class G (general) rated for 2,200 volts | Class C (conductive) does not offer electrical protection

Product Guidelines

Maximum service life of 5 years (shell) & 1 year (suspension) from the time of first use

Never alter or modify the shell or suspension system

Inspect the hard hat each time before use and replace if there is ANY sign of damage

Replace hard hat after it receives a considerable impact

Clean only with mild soap and lukewarm water

Store hard hat in a clean, dry place that is out of direct sunlight

Do not use paints, chemicals, adhesives, gasoline or similar substances on the hard hat

Labels are acceptable if they do not affect a hard hat's protective rating or make it difficult to find damage

There's more to see at **PYRAMEXSAFETY.COM** (P) 800.736.8673 | (F) 901.861.4967

SL Series Sleek Shell head protection meets ANSI Z89.1 (•), Type 1, Class C, G and E. For specific options visit our website or contact your sales representative.