

Solo[®]

ANSI/ISEA Z87.1-2020 + | CAN/CSA Z94.3-20 |
CE/UKCA EN 166

Temples are vented to reduce fogging //
Custom imprinting available

VARIATIONS

Lens and Temples | 1 Variation

S510S Clear



General Specifications	Materials	Part No.	Lens Marking	Temple Marking
Weight: 46 gm 53 gm (Jumbo)	Lens: Polycarbonate	S510S	P Z87+ U6	P Z87+ / P c SEI Z94.3
Lens Base: 4 curve 2.5 curve (Jumbo)	Frame: Polycarbonate			
Lens Size Diagonal: 145 mm	Temples: Polycarbonate			
Lens Size Vertical: 45 mm 50 mm (Jumbo)	Side Shield: Polycarbonate			
Lens Thickness: 2 mm	Hinge: Polycarbonate			
Overall Length (lens - tip): 108 mm	Nose Piece: Polycarbonate			
Overall Width (hinge - hinge): 159 mm 165 mm (Jumbo)				

Lens Marking Symbols

P: Manufacturer's mark
Z87: ANSI standard for eye and face protection devices
+: High impact
UV Filter Transmittance
U6: .01% max effective far UV • .1% max near UV
Visible Light Filters
L3: 18% Max. Visible Light

Temple Marking Symbols

P: Manufacturer's mark
Z87: ANSI standard for eye and face protection devices
+: High impact
c SEI Z94.3: CAN/CSA standard for eye and face protection devices