

Full Frame Foam Padded Safety Glasses

Toccoa™

ANSI CSA



Foam Padding



Anti-Fog



Ultraviolet Protection



Scratch Resistant

FEATURES

Clip-on foam padded carriage
Co-injected temple design with detachable strap

MODEL NO. STYLE NO.

ET010 CHB1010DTMP ● Clear Anti-fog

ET018 CHB1018DTMP ● Sandstone Bronze Anti-fog

ET020 CHB1020DTMP ● Gray Anti-fog

Available in a Carhartt polybag
Carhartt packaging design subject to change



Model No: ET018
Style No: CHB1018DTMP



GENERAL SPECIFICATIONS

Weight: 42 gm
Bridge: 16.32 mm
Lens base: 8 curve
Lens size diagonal: 59.47 mm
Lens size vertical: 60.04 mm
Lens thickness: 2.2 mm
Overall length (lens - tip): 163.2 mm
Overall width (hinge - hinge): 144.3 mm
Closest point between temple tips: 89.5 mm
Closest point between lens: 13.41 mm

MATERIALS

Lens: polycarbonate (PC)
Foam: ethylene-vinyl acetate (EVA)
Frame: polycarbonate (PC)
Temple: polycarbonate (PC)
Temple tips: thermoplastic rubbers (TPR)
Nose pad: ethylene-vinyl acetate (EVA)

LENS + FRAME MARKING SYMBOLS

P: Manufacturer's mark
Z87: ANSI standard for eye and face protection devices
+: High impact
S: Special purpose
c SEI Z94.3: CAN/CSA standard for eye and face protection devices
UG: UV Filter Transmittance .01% max effective far UV • .1% max near UV
X: Tested Anti-fog

MODEL NO.	STYLE NO.	LENS MARKING	FRAME MARKING
ET010	CHB1010DTMP	P Z87 + U6	P Z87 + / P c SEI Z94.3
ET018	CHB1018DTMP	P Z87 + U6 S X	P Z87 + / P c SEI Z94.3
ET020	CHB1020DTMP	P Z87 + U6 S X	P Z87 + / P c SEI Z94.3