

Full Frame Foam Padded Safety Glasses

Toccoa™

ANSI CSA



Foam Padding



Anti-Fog



Ultraviolet Protection



Scratch Resistant

FEATURES

Clip-on foam padded carriage
Co-injected temple design with detachable strap

MODEL NO. STYLE NO.

| | | | |
|-------|-------------|---|---------------------------|
| ET010 | CHB1010DTMP |  | Clear Anti-fog |
| ET018 | CHB1018DTMP |  | Sandstone Bronze Anti-fog |
| ET020 | CHB1020DTMP |  | Gray Anti-fog |

Available in a Carhartt polybag
Carhartt packaging design subject to change



Model No: ET018
Style No: CHB1018DTMP



GENERAL SPECIFICATIONS

Weight: 42 gm
Bridge: 16.32 mm
Lens base: 8 curve
Lens size diagonal: 59.47 mm
Lens size vertical: 60.04 mm
Lens thickness: 2.2 mm
Overall length (lens - tip): 163.2 mm
Overall width (hinge - hinge): 144.3 mm
Closest point between temple tips: 89.5 mm
Closest point between lens: 13.41 mm

MATERIALS

Lens: polycarbonate (PC)
Foam: ethylene-vinyl acetate (EVA)
Frame: polycarbonate (PC)
Temple: polycarbonate (PC)
Temple tips: thermoplastic rubbers (TPR)
Nose pad: ethylene-vinyl acetate (EVA)

LENS + FRAME MARKING SYMBOLS

P: Manufacturer's mark
Z87: ANSI standard for eye and face protection devices
+: High impact
S: Special purpose
c SEI Z94.3: CAN/CSA standard for eye and face protection devices
UG: UV Filter Transmittance .01% max effective far UV • .1% max near UV
X: Tested Anti-fog

| MODEL NO. | STYLE NO. | LENS MARKING | FRAME MARKING |
|-----------|-------------|----------------|-------------------------|
| ET010 | CHB1010DTMP | P Z87 + U6 | P Z87 + / P c SEI Z94.3 |
| ET018 | CHB1018DTMP | P Z87 + U6 S X | P Z87 + / P c SEI Z94.3 |
| ET020 | CHB1020DTMP | P Z87 + U6 S X | P Z87 + / P c SEI Z94.3 |