

**Torser™** ANSI • CE • CSA •



Dielectric // Flexible rubber gasket // Ratchet elastic headband with quick-fit retainer // Passes D3: Droplet and Splash Test // Passes D4: Dust Test // Passes D5: Fine Dust Test // Custom imprinting available

**Black Body | 3 Variations**

- GB10010TM ●●● Clear **H2MAX AF**
- GB10020TM ●●● Gray **H2MAX AF**
- GB10025TM ●● Light Gray **H2MAX AF**



**General Specifications**

Weight: 46.8 gm  
 Bridge: 15 mm  
 Lens base: 8 curve  
 Lens size diagonal: 70.6 mm  
 Lens size vertical: 49.8 mm  
 Lens thickness: 2.0 mm  
 Strap length: 580 mm  
 Overall width (hinge - hinge): 70 mm  
 Closest point between lens: 15 mm  
 Closest point between strap holders: 145 mm

**Materials**

Lens: polycarbonate  
 Strap holder: nylon  
 Headband: polyester  
 Quick-release button: nylon  
 Nosepiece: thermoplastic elastomers  
 Body: polycarbonate & thermoplastic elastomers

**Part No.**

GB10010TM  
 GB10020TM  
 GB10025TM

**Lens Marking**

P Z87 + U6 X  
 P Z87 + U6 L2.5 X  
 P Z87 + U6 L1.7 X

**Frame Marking**

P Z87 + D3 D4 / P c SEI Z94.3  
 P Z87 + D3 D4 / P c SEI Z94.3  
 P Z87 + D3 D4 / P c SEI Z94.3

**Lens Marking Symbols**

P: Manufacturer's mark  
 Z87: ANSI standard for eye and face protection devices  
 +: High impact  
 X: Tested anti-fog  
 UV Filter Transmittance  
 UG: .01% max effective far UV • .1% max near UV  
 Visible Light Filters  
 L1.7: 55% max visible light  
 L2.5: 29% max visible light

**Frame Marking Symbols**

P: Manufacturer's mark  
 Z87: ANSI standard for eye and face protection devices  
 +: High impact  
 D3: Droplet & Splash Test  
 D4: Dust Test  
 c SEI Z94.3: CAN/CSA standard for eye and face protection devices