Torser™ ANSI • CE • CSA •

DIELECTRIC | PASSES D3 DROPLET AND SPLASH TEST | PASSES D4 DUST TEST | PASSES D5 FINE DUST TEST

Dielectric // Flexible rubber gasket // Ratchet elastic headband with quick-fit retainer // Passes D3: Droplet and Splash Test // Passes D4: Dust Test // Passes D5: Fine Dust Test // Custom imprinting available

Black Body | 1 Variation

EGB10020TM •• Grey **H2MAX** AF

WATCH THE **TORSER** VIDEO

General Specifications

Weight: 46.8 gm

Bridge: 15 mm

Lens base: 8 curve

Lens size diagonal: 70.6 mm

Lens size vertical: 49.8 mm

Lens thickness: 2.0 mm

Strap length: 580 mm

Overall width (hinge - hinge): 70 mm

Closest point between lens: 15 mm

Closest point between strap holders: 145 mm

Materials

Lens: polycarbonate

Strap holder: nylon

Headband: polyester

Quick-release button: nylon

Nosepiece: thermoplastic elastomers

Body: polycarbonate & thermoplastic elastomers

Part No.	Lens Marking	Frame Marking
EGB10020TM	5 -2.5 P 1 F K N CE	CE P EN166 F 3 4 5

Lens Marking Symbols

Code-field of use

2 or 3: UV Filter

5 or 6: Solar Filter

Color Perception

C: Unimpaired color perception

Protection Class

1.2 - 6: Degree of visible light filtration

Optical Class

1: High optical quality - no optical distortion

Mechanical Strength

F: Low energy impact, resists a 6 mm, .86 g at 45 m/s

Symbols

P: Manufacturer's mark

K: Resistance to surface damage by fine particles

N: Filter with anti-fog

CE: Certification of European Union

Temple Marking Symbols

Symbols

CE: Certification of European Union

P: Manufacturer's mark

EN166: CE specification for protective eyewear

3: D3 Droplet and Splash Test

4: D4 Dust Test

5: D5 Fine Dust Test

Mechanical Strength

F: Low energy impact