

TRIFECTA®

Provides excellent eye protection for work environments with high humidity that require impact protection // Meets ANSI Z87.1 requirements for screen lenses

Black Frame | 2 Variations

- SB74WMD Black Wire Mesh
- SB76WMD Black Punched Steel



SB74WMD



SB76WMD

MARKINGS

| Part No. | Lens Marking | Temple Marking |
|----------|--------------|----------------|
| SB74WMD | P Z87 | P Z87 |
| SB76WMD | P Z87 | P Z87 |

| Lens Marking Symbols |
|--|
| P: Manufacturer's mark |
| Z87: ANSI standard for eye and face protection devices |

| Temple Marking Symbols |
|--|
| P: Manufacturer's mark |
| Z87: ANSI standard for eye and face protection devices |

SPECIFICATIONS

SB74WMD

| Measurements | Materials |
|---------------------------------------|---------------------------------|
| Weight: 28 gm | Lens: stainless steel |
| PD: 64 mm | Frame: nylon |
| Bridge: 12 mm | Temples: polycarbonate |
| Lens base: 8 curve | Temple tips: polyvinyl chloride |
| Lens size diagonal: 60.5 mm | Screw: stainless steel |
| Lens size vertical: 44.5 mm | |
| Lens thickness: 0.5 mm (SB74WMD) | |
| Overall length (lens - tip): 162 mm | |
| Overall width (hinge - hinge): 140 mm | |
| Closest point between lens: 15 mm | |

SB76WMD

| Measurements | Materials |
|---------------------------------------|---------------------------------|
| Weight: 36 gm | Lens: stainless steel |
| PD: 68 mm | Frame: nylon |
| Bridge: 12 mm | Temples: polycarbonate |
| Lens base: 8 curve | Temple tips: polyvinyl chloride |
| Lens size diagonal: 60.5 mm | Screw: stainless steel |
| Lens size vertical: 44.5 mm | |
| Lens thickness: 0.6 mm | |
| Overall length (lens - tip): 162 mm | |
| Overall width (hinge - hinge): 140 mm | |
| Closest point between lens: 15 mm | |